

County Surveyor's Record, Douglas County, Oregon

52

Dependent Resurvey of $\frac{1}{4}$ portion of Subdivisional Lines, T. 25 S., R. 4 W.

CHAINS

- 22.67 Three-wire transmission line, N. 20° E. and S. 20° W.
- 34.10 Skid road, 10 lks. wide, bears N. and S. 30° W.; continue along barbed wire fence.
- 37.41 Enter swamp, edge bears N. and S.; this swamp drains S. and is the headwaters of Sutherlin Creek.
- 40.71 The $\frac{1}{4}$ sec. cor. of secs. 20 and 29, perpetuated by Wilford N. Haines, with an angle iron, 1x1 ins., 2 ins. above ground, firmly set, with brass cap inscribed, "Survey Point, Wilford N. Haines #239, Drain, Ore.", at record bearing and distance from two original bearing trees, as follows:
- A sawed fir stump, 52 ins. diam., bears N. 69° E., 5 lks. dist., to face, with a faint bark blaze; no scribe marks visible.
- A fir stump hole, fir down and rotted, approx. 40 ins. diam., bears S. 73° E., 24 lks. dist.
- A locally established bearing tree, a sawed fir stump, 25 ins. diam., bears S. 85° W., 40 $\frac{1}{2}$ lks. dist., with BT visible on opened blaze.
- At the corner point
- Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap marked
- T25S R4W
 $\frac{1}{4}$ $\frac{S}{S}$ $\frac{20}{29}$
1957
- from which
- A fir, 8 ins. diam., bears N. 20 $\frac{1}{2}$ ° E., 58 $\frac{1}{2}$ lks. dist., marked $\frac{1}{4}$ S20 BT.
- A fir, 22 ins. diam., bears S. 85 $\frac{1}{4}$ ° W., 139 lks. dist., marked $\frac{1}{4}$ S29 BT.
- Deposit angle iron alongside iron post.
- Corner falls on W. edge of swamp, edge bears N. and S. and in a fence row with fences extending E. and W.
-
- N. 88° 39' W., beginning new measurement.
- Ascend 180 ft. over SE. slope, through logged area.
- 2.00 Abandoned logging road, 10 lks. wide, bears NE. and SW.
- 10.60 Ravine, course SE.; ascend 201 ft. over SE. slope.
- 15.36 Leave logged area, edge bears N. and S.
- 21.04 Point for the W. 1/16 sec. cor. of secs. 20 and 29.
- Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap marked
- W 1/16 $\frac{S}{S}$ $\frac{20}{29}$
1957
- from which
- A fir, 29 ins. diam., bears N. 44 $\frac{1}{2}$ ° W., 44 lks. dist., marked