

County Surveyor's Record, Douglas County, Oregon

53

Dependent Resurvey of Portion of Subdivisional Lines, T. 25 S., R. 4 W.

| | |
|--------|---|
| CHAINS | <p>W 1/16 S20 BT.</p> <p>A fir, 18 ins. diam., bears S. 22½° W., 106 lks. dist., marked W 1/16 S29 BT.</p> <p>Ascend 92 ft. over broken SE. slope.</p> <p>25.58 Ravine, course SE.; ascend 136 ft. over NE. slope.</p> <p>29.82 Spur, slopes SE.; ascend 207 ft. over SE. slope changing to E. slope.</p> <p>40.63 Ridge, bears S. 20° W. and N. 20° E.; descend 41 ft. over W. slope.</p> <p>42.08 The corner of secs. 19, 20, 29 and 30.</p> <p>Land, mountainous. Soil, clay and stony clay. Timber, fir, cedar, hemlock, maple and madrone; undergrowth, hazel, madrone, poison oak, and fir reproduction.</p> <hr/> <p>S. 89° 03' W., between secs. 19 and 30.</p> <p>Descend 833 ft. over W. slope along N. edge of logged area, through heavy timber and light undergrowth,</p> <p>5.00 Edge of timber bears N. 80° W. and E.; enter logged area.</p> <p>19.17 Skid road, bears NE. and SW.</p> <p>27.97 Ravine, course NW.; also skid road, bears NW. and SE.; ascend 12 ft. over NE. slope.</p> <p>29.58 Top of spur, slopes NW.; descend 79 ft. over W. slope.</p> <p>32.02 Dirt access road at edge of logged area, 17 lks. wide, bears N. and S.</p> <p>32.52 Sutherlin Creek, 10 lks. wide, course N.; ascend 159 ft. over E. slope changing to SE. slope through dense undergrowth.</p> <p>38.57 The ¼ sec. cor. of secs. 19 and 30, restored at record distances from the original bearing trees,</p> <p style="padding-left: 40px;">A decayed and burned fir stump, 35 ins. diam., bears N. 41½° E., 36 lks. dist., with no scribe marks visible on a burned and rotten blaze. (Record bearing N. 40° E.)</p> <p style="padding-left: 40px;">A fir, 29 ins. diam., bears S. 42° E., 8 lks. dist., with no scribe marks visible on a burned and chopped out blaze. (Record bearing, S. 50° E.)</p> <p>At the corner point</p> <p>Set iron post, 28 ins. long., 2½ ins. diam., 26 ins. in the ground, with brass cap marked</p> <p style="text-align: center;">T25S R4W</p> <p style="text-align: center;">¼ S 19 ¼ S 30</p> <p style="text-align: center;">1957</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears N. 7° W., 50 lks. dist., marked ¼ S19 BT.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 21° W., 33 lks. dist., marked ¼ S30 BT.</p> <p>N. 89° 42' W., beginning new measurement along N. edge of logged area.</p> |
|--------|---|