

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines, T. 25 S., R. 4 W.

CHAINS

Reset the angle iron alongside the iron post.

Corner falls at the edge of logged area, bears N. and E.


N. 1° 42' E., beginning new measurement.

Ascend 263 ft. over S. slope between old growth and logged area.

9.63 Ridge, bears E. and W.; descend 369 ft. over N. slope through heavy reproduction.

20.33 Point for N. 1/16 sec. cor. of secs. 19 and 20.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked



from which

A fir, 13 ins. diam., bears S. 64½° E., 163 lks. dist., marked NL/16 S20 BT.

A fir, 40 ins. diam., bears N. 30¼° W., 94 lks. dist., marked NL/16 S19 BT.

Descend 70 ft. over N. slope along W. edge of logged area.

21.95 Ravine, course NW.; descend 136 ft. along W. slope changing to NW. slope.

24.90 Branch, 2 lks. wide, course W.; ascend 118 ft. over SW. slope through timber and dense undergrowth.

28.27 Spur, slopes W.; descend 146 ft. over NW. slope.

33.87 Dry branch, 10 lks. wide, course S. 60° W.; ascend 191 ft. over SE. slope.

40.66 The cor. of secs. 18, 17, 19 and 20, determined at record distances from the remaining original bearing trees,


An uprooted fir snag, 80 ins. diam., bears N. 32° E., 27 lks. dist., with no marks remaining on a burned out blaze.

A fir, 36 ins. diam., bears S. 42° E., 64 lks. dist., marked with healed blaze; also bark scribed S 8 visible.

A fir, 59 ins. diam., bears S. 54¼° W., 62 lks. dist., marked with a healed blaze; also bark scribed S 19 visible.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked



from which

A fir, 32 ins. diam., bears N. 61° E., 138½ lks. dist., marked T25S R4W S17 BT.

A fir, 13 ins. diam., bears N. 70° W., 57 lks. dist., marked