

Dependent Resurvey of Portion of Subdivisional Lines of T. 25 S., R. 4 W.

CHAINS

T25S R4W S18 BT.

From this point, an angle iron, 1x1 ins., protruding 8 ins. above ground, bears S. 80° E., 3½ lks. dist., with brass cap marked, "Wilford N. Haines, #239 Survey Point, Drain, Ore."

Land, mountainous. Soil, rocky clay and loam. Timber, fir, hemlock, cedar and maple; undergrowth, vinemaple, hazel, dogwood, rhododendron and reproduction.

From the corner of secs. 16, 17, 20 and 21.

N. 88° 03' W., between secs. 17 and 20.

Ascend 477 ft. over SE. slope, through scattering timber and dense undergrowth.

20.04 Point for the E. 1/16 sec. cor. of secs. 17 and 20.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

E 1/16 $\frac{S\ 17}{S\ 20}$

1957

from which

A fir, 18 ins. diam., bears N. 3¼° W., 147½ lks. dist., marked E 1/16 S 17 BT.

A fir, 17 ins. diam., bears S. 9° E., 60 lks. dist., marked E 1/16 S 20 BT.

Ascend 8 ft. over SE. slope.

20.33 Spur, slopes S.; descend 34 ft. over SW. slope.

22.77 Ravine, drains SE.; ascend 314 ft. over E. slope changing to SE. slope.

40.08 The ¼ sec. cor., of secs. 17 and 20, perpetuated by an angle iron, 36x1x1 ins., firmly set 24 ins. in the ground, with brass cap marked "Wilford N. Haines, #239, Survey point, Drain, Ore.", from which the original bearing tree:

A fir snag, 29 ins. diam., bears S. 70° E., 52 lks. dist., with scribe marks ¼ S visible on partly opened blaze.

and a local bearing tree

An uprooted fir, 14 ins. diam., bears N. 37° E., 36 lks. dist., with scribe marks CS visible on partly opened blaze.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

T25S R4W
 $\frac{1}{4}\ \frac{S\ 17}{S\ 20}$

1957

from which

A fir, 21 ins. diam., bears N. 83° E., 149½ lks. dist., marked ¼ S 17 BT.

A cedar, 14 ins. diam., bears S. 41½° W., 49½ lks. dist., marked ¼ S 20 BT.

Reset the angle iron alongside the iron post.