

County Surveyor's Record, Douglas County, Oregon

57

Dependent Resurvey of Portion of Subdivisional Lines, T. 25 S., R. 4 W.

CHAINS

N. 89° 35' W., beginning new measurement.

Ascend 40 ft. over E. slope, through heavy timber and light undergrowth.

3.36 Top of ridges, extending N. 80° E., S. 30° W. and NW.; descend 399 ft. over W. slope.

5.20 Dirt logging road, bears N. 20° E. and S. 20° W.

14.23 Ravine, drains N. 80° W.; descend 236 ft. over NW. slope.

19.84 Dry branch, 5 lks. wide, course SW.; ascend 77 ft. over SE. slope.

23.92 Top of ascent, slopes S.; descend 216 ft. over SW. slope. changing to W. slope.

35.50 Dry branch, course S.; ascend 95 ft. over SE. slope.

39.56 The cor. of secs. 17, 18, 19 and 20.

Land, mountainous. Soil, rocky clay and loam. Timber, fir, cedar, hemlock, maple, madrone, chinquapin and oak; undergrowth, vinemaple, dogwood, rhododendron, poison oak, hazel, berry vines and reproduction.

S. 89° 21' W., between secs. 18 and 19.

Ascend 120 ft. over SE. slope along S. edge of logged area, through heavy timber and light undergrowth.

7.42 Top of ascent slopes S.; descend 79 ft. over SW. slope.

10.70 Head of ravine, course S.; ascend 6 ft. over SE. slope.

13.07 Spur, slopes S.; descend 167 ft. over SW. slope.

19.945 Point for the E 1/16sec. cor. of secs. 18 and 19.

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap marked

$$E \frac{1}{16} \begin{array}{l} S \ 18 \\ S \ 19 \end{array}$$

1957

from which

A fir, 27 ins. diam., bears N. 74° W., 83 lks. dist., marked EL/16 S18 BT.

A fir, 25 ins. diam., bears S. 44° 45' E., 124½ lks. dist., marked EL/16 S19 BT.

From this point, a stone 24x36 ins., protruding 12 ins. above ground, with chisel marks X S18W SW COR on upturned face, bears SW., 7 lks. dist., from which a bearing tree:

A fir snag, 37 ins. diam., bears S. 66° E., 47 lks. dist., with scribe marks S18WBT.

Descend 2 ft. along S. slope.

27.48 Low spur, slopes SW.; descend 202 ft. over W. slope.

39.89 Point for the ¼ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked