

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines, T. 25 S., R. 4 W.

CHAINS

T25S R4W

$\frac{1}{4}$  S 18  
 $\frac{1}{4}$  S 19

1957

from which

A white oak, 16 ins. diam., bears N.  $41\frac{1}{2}^\circ$  E., 163 lks. dist., marked  $\frac{1}{4}$  S18 BT.

A fir, 9 ins. diam., bears S.  $57^\circ$  E.,  $46\frac{1}{2}$  lks. dist., marked  $\frac{1}{4}$  S19 BT.

Corner falls at the edge of timber, bears NE. and SE.

Descend 74 ft. over gradual W. slope through open pasture land.

46.50 Woven-wire fence, bears N. and S.; enter cultivated field.

55.52 Intermittent creek, 2 lks. wide, course N.  $50^\circ$  W.; descend 51 ft. over gentle W. slope of valley bottom.

68.20 Woven-wire fence at edge of cultivated field, bears N.  $35^\circ$  W. S.  $35^\circ$  E.

68.45 Gravelled road, 20 lks. wide, bears N.  $35^\circ$  W. and S.  $35^\circ$  E.; enter open pasture land.

68.90 Power and telephone line bears N.  $35^\circ$  W. and S.  $35^\circ$  E.

78.91 The corner of secs. 13, 18, 19 and 24 on W. bdy. of Tp.

Land, E. half mountainous; W. half, valley bottom. Soil, E. half rocky clay and loam; valley loam. Timber, fir, cedar, hemlock, madrone, white and black oak, ash and maple; undergrowth, vine maple, hazel, scrub oak, willow and reproduction.

From the corner of secs. 17, 18, 19 and 20.

N.  $0^\circ 03'$  E. between secs. 17 and 18.

Ascend 344 ft. over SE. slope, through heavy timber along E. edge of logged area.

15.26 Ridge, bears E. and W.; descend 194 ft. over N. slope.

18.85 Ravine, course NW.; descend 49 ft. along W. slope.

21.10 Ravine, course W.; descend 94 ft. over W. slope changing to NW. slope.

24.86 Ravine, course W.; ascend 195 ft. over SW. slope.

32.08 Spur, slopes W.; descend 108 ft. over N. slope.

35.03 Ravine, course W.; ascend 32 ft. over W. slope.

39.73 Point for the  $\frac{1}{4}$  sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$ " diam., 14 ins. in the ground, to solid rock, in a mound of stone, 3 ft. base to top, with brass cap marked

T25S R4W

$\frac{1}{4}$   
S 18 | S 17

1957

from which