

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines, T. 25 S., R. 4 W.

CHAINS

A fir, 22 ins. diam., bears N. $69\frac{1}{2}^{\circ}$ E., 52 lks. dist., marked $\frac{1}{4}$ S17 BT.

A fir, 26 ins. diam., bears N. $48\frac{1}{4}^{\circ}$ W., 115 $\frac{1}{2}$ lks. dist., marked $\frac{1}{4}$ S18 BT.

Descend 1 ft. along W. slope.

40.70 Head of ravine, course SW.; ascend 178 ft. over SE. slope changing to S. slope.

46.53 Spur, slopes SW.; ascend 38 ft. along W. slope.

50.48 Spur ridge, bears N. 30° W. and S. 30° E.; descend 128 ft. over NE. slope, through old logged area.

52.47 Barbed wire fence, bears N. 30° W. and S. 30° E.

59.595 Point for the N 1/16 sec. corner of secs. 17 and 18.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

N 1/16
S 18 | S 17
1957

from which

A fir, 7 ins. diam., bears S. $71\frac{1}{4}^{\circ}$ E., 62 $\frac{1}{2}$ lks. dist., marked N 1/16 S17 BT.

A fir, 17 ins. diam., bears N. $13\frac{1}{4}^{\circ}$ W., 46 lks. dist., marked N 1/16 S18 BT.

Descend 312 ft. over NE. slope, through scattering timber and dense undergrowth.

79.46 Point for the cor. of secs. 7, 8, 17 and 18, perpetuated by an iron post, 36 ins. long, 1 $\frac{1}{2}$ ins. diam., protruding 18 ins. above ground, and a weathered fir stake, 2 ft. long, 2 ins. square protruding 12 ins. above the ground, scribed 7 8 17 18, from which the remains of the original bearing trees:

A stump hole, bears N. 80° W., 8 lks. dist.

and trees marked by local surveyors

A sawed fir stump, 51 ins. diam., bears N. $63^{\circ} 45'$ E., 159 $\frac{1}{2}$ lks. dist., with lower end of healed blaze visible.

A madrone, 26 ins. diam., bears S. $60\frac{1}{2}^{\circ}$ E., 92 lks. dist., with rotted out blaze.

A sawed fir stump, 27 ins. diam., bears S. 70° W., 78 $\frac{1}{2}$ lks. dist. bark scribed W S BT.

A sawed fir stump, 21 ins. diam., bears N. 48° W., 57 $\frac{1}{2}$ lks. dist. bark scribed S S R4W BT.

At the corner point,

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap marked.

T25S R4W
S 7 | S 8
S 18 | S 17
1957

from which