

County Surveyor's Record, Douglas County, Oregon

62

Dependent Resurvey of Portion of Subdivisional Lines, T. 25 S., R. 4 W.

CHAINS

- 38.87 From this point, the NW. cor. of a wood frame shed bears south, 120 lks. dist., dimensions 8x9 ft., long side bears S. 75° E.; also a chicken house bears S., 24 lks. dist., dimensions 15x17 ft., long side bears S. 70° E.
- 40.38 Point for the $\frac{1}{4}$ sec. cor., of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins diam., 24 ins. in the ground, with brass cap marked
- T25S R4W
 $\frac{1}{4}$ $\frac{S 8}{S 17}$
1957
- from which
- A fir, 24 ins. diam., bears N. 65° W., $650\frac{1}{2}$ lks. dist., marked $\frac{1}{4}$ S8 BT.
- A maple, 16 ins. diam., bears S. 61° W., $183\frac{1}{2}$ lks. dist., marked $\frac{1}{4}$ S17 BT.
- Corner falls on N. bank of fish pond, 60 lks. wide, 2 ft. deep; center bears south, 43 lks. dist.
- 40.67 Woven-wire fence bears N. 55° E. and S. 55° W.
- 42.34 Ditch, 5 ft. deep, 6 lks. wide, drains NW. curving to N.; also base of slope and edge of field bears NW. and SE.; ascend 119 ft. over NE slope, through scattered timber and dense undergrowth.
- 43.97 Abandoned irrigation ditch, 4 ft. deep, 9 lks. wide, bears N. 30° W. and S. 30° E.
- 52.75 Top of ascent, slopes N.; descend 37 ft. over NW. slope.
- 55.71 Ravine, course NW.; ascend 25 ft. over NE. slope.
- 57.11 Dirt road, 15 lks. wide, bears N. 35° E. and S. 35° W.
- 57.74 Top of ascent slopes N.; descend 18 ft over NW. slope.
- 59.34 Branch, 2 lks. wide, course N.; ascend 45 ft. over E. slope.
- 60.57 Point for the W $\frac{1}{16}$ sec. cor. of secs. 8 and 17.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked
- W $\frac{1}{16}$ $\frac{S 8}{S 17}$
1957
- from which
- A madrone, 8 ins. diam., bears N. $59\frac{1}{2}$ ° E., 39 lks. dist., marked W $\frac{1}{16}$ S8 BT.
- A fir, 18 ins. diam., bears S. $40\frac{1}{2}$ ° W., 114 lks. dist., marked W $\frac{1}{16}$ S17 BT.
- Ascend 13 ft. over N. slope.
- 64.38 End of new woven-wire fence, bears W.; also head of ravine, drains NE.; ascend 179 ft. over E. slope.
- 68.64 Dirt road, 20 lks. wide, bears N. 30° W. and S. 30° E.