

County Surveyor's Record, Douglas County, Oregon

64

Dependent Resurvey of Portion of Subdivisional Lines, T. 25 S., R. 4 W.

CHAINS 49.95	Foot of descent, slopes W.; ascend 85 ft. over S. slope.
60.86	Ridge, bears NW. and SE.; enter timber, edeg bears E. and W.; descend 117 ft. over NE. slope changing to N. slope.
63.45	Woven-wire and barbed-wire fence, bears E. and W.
65.75	Foot of descent, slopes NW.; ascend 11 ft. over SW. slope.
69.45	Spur, slopes NW.; descend 222 ft. over NW. slope.
83.92	The $\frac{1}{4}$ sec. cor. of secs. 12 and 13. Land, rolling hills. Soil, black clay loam and stony clay. Timber, fir, cedar, maple and madrone; undergrowth, hazel, vinemaple, salal, dogwood, Oregon grape, ocean spray, manzanita, poison oak, and fir reproduction.
	From the $\frac{1}{4}$ sec. cor. of secs. 13 and 18 on E. bdy. of Tp. S. 88° 39' W., on the E. and W. center line of sec. 13. Ascend 147 ft. over NE. slope, through heavy timber and dense undergrowth.
5.87	Spur, slopes N.; descend 237 ft. over NW. slope.
14.88	Foot of descent, slopes N.; ascend 92 ft. over broken NE. slope.
18.03	Abandoned dirt road, 20 lks. wide, bears N. and S. curving to E.
19.40	Point for the center E 1/16 sec. cor. of sec. 13. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap marked <div style="text-align: center;"> $\frac{CE\ 1/16}{S\ 13}$ 1958 </div> <i>See BLM Line notes VOL. 53 Pgs 20176-7 for 1998 Rehabilitation</i> from which A fir, 13 ins. diam., bears N. 64 $\frac{1}{2}$ ° E., 76 lks. dist., marked CE 1/16 S13 BT. A fir, 11 ins. diam., bears S. 70 $\frac{1}{4}$ ° W., 7 lks. dist., marked CE 1/16 S13 BT. Ascend 44 ft. over broken NE. slope.
21.80	Spur, slopes N.; descend 402 ft. over NW. slope.
38.80	The center $\frac{1}{4}$ sec. cor. of sec. 13. Enter logged area, bears N. and S. Descend 140 ft. over NW. slope.
45.40	Dirt logging road, 20 lks wide, bears NE. and SW. curving to W.
50.65	Foot of descent, slopes S.; ascend 82 ft. over SE. slope.
60.40	Spur, slopes S.; descend 164 ft. over SW. slope.
66.15	Graveled and maintained road, 25 lks. wide, bears NW. and SE.
66.63	Woven-wire and barbed-wire fence, bears NW. and SE.
70.00	Woven-wire and barbed-wire fence, bears NW. and SE.
71.50	Creek, 5 lks. wide, course N.; descend 3 ft. over gentle N. slope.