

County Surveyor's Record, Douglas County, Oregon

3

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 19 S., R. 8 W.

CHAINS

24.10 Dry stream bed, 3 lks. wide, course N. 55° E.; ascend 58 ft. along E. slope.

33.40 Top of ascent, slopes E.; descend 123 ft. over N. slope.

36.65 Mill Creek, 15 lks. wide, course E.; ascend 17 ft. over creek bottom.

40.65 The cor. of secs. 13, 14, 23 and 24, determined at record bearing and distance from each of the remaining original bearing trees, as follows:

An uprooted cedar, 30 ins. diam., bears S. 65° E., 6 lks. dist., with scribe marks 8W S24 visible on burned blaze.

A maple, 55 ins. diam., bears S. 10° W., 100 lks. dist., with a decayed blaze.

A decayed cedar stump, 20 ins. diam., bears N. 62½° W., 83 lks. dist., with no marks remaining.

At the corner point

Set an iron post, 28 ins. long, 2½ ins diam., 24 ins. in the ground, with brass cap marked

T19S R8W
S 14 | S 13
S 23 | S 24
1958

from which new bearing trees:

A cedar, 20 ins. diam., bears N. 50° E., 33½ lks. dist., marked T19S R8W S13 BT.

A cedar, 13 ins. diam., bears S. 11° E., 33 lks. dist., marked T19S R8W S24 BT.

A hemlock, 13 ins. diam., bears S. 29½° W., 92½ lks. dist., marked T19S R8W S23 BT.

A fir, 12 ins. diam., bears N. 42° W., 57 lks. dist., marked T19S R8W S14 BT.

Land, mountainous. Soil, sandy clay loam. Timber, fir, hemlock, cedar, maple, alder and madrone. Undergrowth, vine maple, young conifers, red huckleberry, salmonberry, hazel, arrowwood, salal, and sword fern.

From the cor. of secs. 22, 23, 26 and 27, determined at record bearing and distance from each of the remaining original bearing trees, as follows:

A fir, 45 ins. diam., bears N. 12° E., 185 lks. dist., with a burned out blaze.

A fir snag, 30 ins. diam., bears S. 19½° E., 148 lks. dist., with healed blaze; I open and uncover scribe marks T19S R8W S26 BT.

A decayed fir stump, 14 ins. diam., bears S. 14° 45' W., 212 lks. dist., with no marks remaining.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

T19S R8W
S 22 | S 23
S 27 | S 28
1958

Fd. by:
M. KRUSH
11/11/82
M 93-36