

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 19 S., R. 8 W.

CHAINS

from which new bearing trees:

A fir, 8 ins. diam., bears N.  $29\frac{1}{4}^{\circ}$  E., 21 lks. dist., marked T19S R8W S23 BT.

A fir, 9 ins. diam., bears S.  $45^{\circ} 45'$  E., 23 lks. dist., marked T19S R8W S26 BT.

A fir, 10 ins. diam., bears S.  $35\frac{1}{2}^{\circ}$  W., 8 lks. dist., marked T19S R8W S27 BT.

A fir, 10 ins. diam., bears N.  $12\frac{1}{2}^{\circ}$  W., 25 lks. dist., marked T19S R8W S22 BT.

N.  $1^{\circ} 17'$  E., bet. secs. 22 and 23.

Descend 141 ft. over N. slope, through heavy timber and dense undergrowth.

4.60 Ravine, course N.  $85^{\circ}$  W.; ascend 307 ft. along broken W. slope.

37.25 Spur, slopes N.  $30^{\circ}$  W.; descend 230 ft. over N. slope.

40.81 The  $\frac{1}{4}$  sec. cor. of secs. 22 and 23, determined at the record bearing and distance from each of the original bearing trees, as follows:

A burned fir snag, 16 ins. diam., bears S.  $24^{\circ}$  E., 46 lks. dist., with scribe marks  $\frac{1}{4}$  S BT visible on unburned face of blaze.

The decayed remains of a fir stump, size indeterminate, bears S.  $69\frac{1}{2}^{\circ}$  W., 57 lks. dist., with no marks remaining.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap marked

T19S R8W  
S 22  $\frac{1}{4}$  S 23  
1958

from which new bearing trees:

A fir, 32 ins. diam., bears N.  $88\frac{1}{2}^{\circ}$  E., 22 lks. dist., marked  $\frac{1}{4}$  S23 BT.

A fir, 12 ins. diam., bears N.  $77\frac{1}{4}^{\circ}$  W., 37 lks. dist., marked  $\frac{1}{4}$  S22 BT.

N.  $1^{\circ} 12'$  W., beginning new measurement.

Descend 77 ft. over N. slope.

1.05 Ravine, course N.  $20^{\circ}$  E.; descend 29 ft. along E. slope.

6.20 Ravine, course S.  $70^{\circ}$  E.; ascend 115 ft. over S. slope.

8.80 Spur, slopes S.  $80^{\circ}$  E.; descend 412 ft. over NE. slope.

22.13 Mill Creek, 10 lks. wide, course N.  $65^{\circ}$  E.; ascend 208 ft. over SE. slope.

34.10 Top of ascent, slopes E.; descend 226 ft. over NE. slope.

41.06 The cor. of secs. 14, 15, 22 and 23, determined at record distance

Fd. by:  
M. KRUSH  
11/11/82  
M 93-36