

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 19 S., R. 8 W.

CHAINS

from each of the remaining original bearing trees, as follows:

A maple, 44 ins. diam., bears S. 76° E., 100 lks. dist., with decayed blaze facing the corner point. (Record bearing, N. 85° E.)

A maple, 42 ins. diam., bears S. 24½° E., 92 lks. dist., with a healed blaze facing the corner point; I open and uncover axe marks but no scribe marks on decayed face of blaze. (Record bearing, S. 29° E.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap marked

T19S R8W
S 15 | S 14
S 22 | S 23
1958

Fd by:
M. KRUSH
11/1/02
M. 93-36

from which new bearing trees:

A cedar, 10 ins. diam., bears N. 76° E., 40 lks. dist., marked T19S R8W S14 BT.

A cedar, 26 ins. diam., bears S. 54½° E., 4 lks. dist., marked T19S R8W S23 BT.

A fir, 36 ins. diam., bears S. 40° W., 72½ lks. dist., marked T19S R8W S22 BT.

A cedar, 23 ins. diam., bears N. 55½° W., 97 lks. dist., marked T19S R8W S15 BT.

Land, mountainous. Soil, sandy clay loam. Timber, fir, hemlock, cedar, maple, alder, cascara, madrone, and yew. Undergrowth, vine maple, arrowwood, red huckleberry, young conifers, salmon-berry, salal, sword fern, and bracken.

From the cor. of secs. 13, 14, 23 and 24.

N. 88° 02' W., bet. secs. 14 and 23.

Ascend 5 ft. over creek bottom, through heavy timber and dense undergrowth.

16.40 Mill Creek, 10 lks. wide, course S. 20° E., ascend 22 ft. along N. slope.

21.70 Dry stream bed, 3 lks. wide, course N.; ascend 243 ft. over NE. slope.

30.15 Top of ascent, slopes N.; descend 91 ft. over NW. slope.

39.02 The ¼ sec. cor. of secs. 14 and 23, determined at record bearing and distance from each of the original bearing trees as follows:

A fir snag, 35 ins. diam., bears N. 14½° E., 23 lks. dist., with burned out blaze facing the corner point.

A fir snag, 60 ins. diam., bears S. 41° 45' W., 45 lks. dist., plainly blazed and healed.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in ground, and in a small mound of stone, to top, with brass cap marked