

## County Surveyor's Record, Douglas County, Oregon

6

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 19 S., R. 8 W.

CHAINS

T19S R8W

$$\frac{1}{4} \begin{array}{l} S 14 \\ S 23 \end{array}$$

1958

From which new bearing trees:

A fir, 21 ins. diam., bears N.  $69^{\circ} 45'$  W., 91 lks. dist., marked  $\frac{1}{4}$  S14 BT.

A fir, 15 ins. diam., bears S.  $55\frac{1}{2}^{\circ}$  W., 55 lks. dist., marked  $\frac{1}{4}$  S23 BT.

N.  $86^{\circ} 24'$  W., beginning new measurement.

Descend 102 ft. over NW. slope.

3.40 Dry stream bed, 4 lks. wide, course N.; asc. 165 ft. over E. slope.

6.70 Spur, slopes N.; descend 170 ft. over NW. slope.

16.80 Mill Creek, 10 lks. wide, course N.  $80^{\circ}$  E., ascend 21 ft. along creek bottom.

23.10 Edge of creek bottom, bears N.  $50^{\circ}$  E. and S.  $50^{\circ}$  W.; ascend 188 ft. along broken S. slope.

32.95 Top of ascent, slopes S.; descend 188 ft. over SW. slope.

40.35 Dry stream bed, 3 lks. wide, course S.  $60^{\circ}$  E.; ascend 48 ft. over E. slope.

41.11 The cor. of secs. 14, 15, 22 and 23.

Land, mountainous. Soil, sandy clay loam. Timber, fir, hemlock, cedar, maple, alder, and cascara. Undergrowth, vine maple, salmonberry, red huckleberry, hazel, salal, and sword fern.

Remonumentation of the Corner of Sections 10, 11,  
14 and 15, T. 19 S., R. 8 W.  
(Original survey by Charles M. Collier in 1891)

The cor. of secs. 10, 11, 14 and 15, is determined at record bearing and distance from each of the original bearing trees, as follows:

A living but partly uprooted fir, 14 ins. diam., bears N.  $4\frac{1}{2}^{\circ}$  E., 30 lks. dist., with scribe marks R8W S visible on opened blaze.

A fir, 30 ins. diam., bears S.  $22\frac{1}{4}^{\circ}$  E., 24 lks. dist., plainly blazed and healed.

A decayed fir stump, 24 ins. diam., bears S.  $46\frac{1}{2}^{\circ}$  W., 34 lks. dist., with no marks remaining.

An uprooted fir, 14 ins. diam., bears N.  $71\frac{1}{2}^{\circ}$  W., 40 lks. dist., with a healed blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap marked

T19S R8W  

$$\begin{array}{l} S 10 | S 11 \\ S 15 | S 14 \end{array}$$
 1958

from which new bearing trees: