

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines of T. 21 S., R. 11 W.

CHAINS	
1.65	Dry bed of stream, 5 lks. wide, course N. 10° W., asc. 110 ft. over NE. slope.
4.55	Spur, slopes N. 30° E.; desc. 55 ft. over NW. slope.
7.20	Ravine, course NE.; asc. 330 ft. over SE. slope.
14.75	Spur ridge, bears N. 5° W. and S. 5° E.; desc. 340 ft. over W. slope.
21.80	Dry bed of stream, 2 lks. wide, course N. 25° W.; asc. 125 ft. over NE. slope.
26.00	Spur, slopes N.; desc. 155 ft. over NW. slope.
29.70	Dry bed of stream, 2 lks. wide, course N. 10° E.; asc. 150 ft. over NE. slope, changing to N. slope.
39.00	Ravine, course N. 50° E.; asc. 50 ft. over SE. slope.
40.12	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 2 ins. in the ground, to bedrock in a mound of stone, 4 ft. base, to top, with brass cap marked T21S R11W $\frac{1}{4} \begin{array}{l} S 13 \\ S 24 \end{array}$ 1957 from which A fir, 20 ins. diam., bears N. 15° W., 77 lks. dist., marked $\frac{1}{4}$ S13 BT. A cedar, 48 ins. diam., bears S. 42° E., 19 lks. dist., marked $\frac{1}{4}$ S24 BT. The $\frac{1}{4}$ sec. cor. is located at bottom of the face of a ledge of sandstone, 6 ft. high, bears E. and W. Ascend 230 ft. over SE. slope.
45.20	Ridge, the divide between Murphy Creek and Otter Creek, bears NW. and SE.; a spur, slopes N. 10° E.; desc. 180 ft. over SW. slope, changing to broken S. slope.
50.50	Enter burned area; edge bears NE. and SW.; thence through partly dead timber and undergrowth.
52.50	Head of ravine, course S.; asc. 180 ft. over SE. slope.
58.40	Spur ridge, bears N. 20° E. and S. 20° W.; desc. 90 ft. over SW. slope.
60.18	Point for the W. $\frac{1}{16}$ sec. cor. of secs. 13 and 24. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap marked $W \frac{1}{16} \begin{array}{l} S 13 \\ S 24 \end{array}$ 1957 from which A fir, 18 ins. diam., bears N. 34° W., 42 lks. dist., marked W $\frac{1}{16}$ S13 BT. A fir, 21 ins. diam., bears S. 4° E., ., $43\frac{1}{2}$ lks. dist., marked W $\frac{1}{16}$ S24 BT.