

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines of T. 21 S., R. 11 W.

CHAINS

The 1/16 sec. cor. is located in a fire trail at edge of burned area; Trail bears NE. and SW.

Descend 225 ft. over SW. slope, through heavy green timber and dense undergrowth.

65.50 Head of ravine, course S. 30° W.; asc. 5 ft. along S. slope.

67.30 Spur, slopes S. 50° W.; descend 130 ft. over W. slope.

69.85 Dry bed of stream, 2 lks. wide, course S. 15° W.; asc. 85 ft. over SE. slope.

72.20 Spur, slopes S.; desc. 100 ft. over SW. slope.

75.40 Dry bed of stream, 3 lks. wide, course S. 10° E.; asc. 110 ft. over SE. slope, changing to S. slope.

80.24 Point for the cor. of secs. 13, 14, 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 2 ins. in the ground, to bedrock in a mound of stone, 6 ft. base, to top, with brass cap marked

T21S R11W  
S 14 | S 13  
S 23 | S 24  
1957

from which

A fir, 50 ins. diam., bears N. 42° E., 46 lks. dist., marked T21S R11W S13 BT.

A maple, 10 ins. diam., bears S. 40° E., 41 lks. dist., marked T21S R11W S24 BT.

A fir, 50 ins. diam., bears S. 58½° W., 48 lks. dist., marked T21S R11W S23 BT.

A fir, 20 ins. diam., bears N. 74° W., 100 lks. dist., marked T21S R11W S14 BT.

The sec. cor. is located 10 lks. E. of a ravine, course SE., at base of a sandstone ledge, 5 ft. high, faces S.

From this point the ¼ sec. cor. of secs. 23 and 24, bears S. 8° 02' E., 40.39 chs. dist., mounmented with a sandstone, 8x8x8 ins., firmly set 6 ins. in the ground, plainly marked ¼ on W. face, showing no evidence of having been disturbed, and substantiated by an old blaze on a snag about 3 chs. southerly, topography to the north and south and a small mound of stone at the W. side.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a small mound of stone, to top, with brass cap marked

T21S R11W  
¼  
S 23 | S 24  
1957

from which

A fir, 26 ins. diam., bears N. 27¼° E., 40 lks. dist., marked ¼ S24 BT.