

## County Surveyor's Record, Douglas County, Oregon

## Dependent Resurvey of Portion of Subdivisional Lines of T. 21 S., R. 11 W.

## CHAINS

A fir, 16 ins. diam., bears N.  $51\frac{1}{2}^{\circ}$  W.,  $15\frac{1}{2}$  lks. dist., marked  $\frac{1}{4}$  S13 BT.

A fir, 8 ins. diam., bears S.  $79^{\circ} 20'$  W., 534 lks. dist., blazed on N., S., E., and W. sides, marked as approx.  $\frac{1}{4}$  sec. cor. with lumber crayon.

Reset the sandstone alongside and E. of the iron post.

The  $\frac{1}{4}$  sec. cor. is located 7 lks. S. of a small gully, drains S.  $60^{\circ}$  W.

Also from the cor. of secs. 13, 14, 23 and 24, the cor. of secs. 15, 16, 21 and 22, bears N.  $89^{\circ} 00'$  W., 160.16 chs. dist., remonumented with an iron pipe, 2 ft. long,  $1\frac{1}{4}$  ins. diam., driven 18 ins. in the ground, from which the original bearing trees:

A cedar, 66 ins. diam., bears N.  $54^{\circ}$  E., 20 lks. dist., plainly blazed and healed. (Record bearing, N.  $52^{\circ}$  E.)

An alder, 20 ins. diam., bears S.  $42^{\circ}$  E., 24 lks. dist., plainly blazed and healed. (Record distance, 31 lks.)

A hemlock snag, 16 ins. diam., bears S.  $6\frac{1}{2}^{\circ}$  W., 15 lks. dist., with scribe marks "BT" visible on opened blaze. (Record bearing, S.  $10^{\circ}$  W.)

A hemlock snag, 36 ins. diam., bears N.  $56^{\circ}$  W., 35 lks. dist., with scribe marks "R11W" and "BT" visible on opened blaze. (Record distance, 37 lks.)

At the corner point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap marked

T21S	R11W
S 16	S 15
S 21	S 22
1957	

from which new bearing trees:

A hemlock, 9 ins. diam., bears S.  $12^{\circ}$  E., 35 lks. dist., marked T21S R11W S22 BT.

A hemlock, 16 ins. diam., bears S.  $27\frac{1}{4}^{\circ}$  W., 133 lks. dist., marked T21S R11W S21 BT.

A crooked cedar, 17 ins. diam., bears N.  $33\frac{3}{4}^{\circ}$  W., 181 lks. dist., marked T21S R11W S16 BT.

Reset the iron pipe alongside the iron post.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, maple, and alder.

Undergrowth, vine maple, hazel, arrowwood, salmonberry, thimbleberry, rhododendron, and huckleberry.

N.  $0^{\circ} 58'$  W., bet. secs. 13 and 14.

Ascend 210 ft. over steep S. slope, changing to SE. slope, through heavy timber and dense undergrowth.

5.65 Top of ascent on E. slope; desc. 70 ft. over NE. slope.

8.50 Ravine, course E.; asc. 230 ft. over S. slope, through partly burned area.