

County Surveyor's Record, Douglas County, Oregon

5

Dependent Resurvey of Portion of Subdivisional Lines of T. 21 S., R. 11 W.

| CHAINS | |
|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 13.00 | Ridge, the divide bet. Otter Creek and Cassidy Creek, bears E. and W.; desc. 220 ft. over N. slope. |
| 17.35 | Ravine, course N. 70° E.; asc. 70 ft. over SE. slope. |
| 20.00 | Point for the S. 1/16 sec. cor. of secs. 13 and 14. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked <div style="text-align: center;"> S 1/16 S 14 S 13 1957 </div> from which A fir, 20 ins. diam., bears N. 8½° E., 12 lks. dist., marked S 1/16 S13 BT. A fir, 24 ins. diam., bears S. 34½° W., 7½ lks. dist., marked S 1/16 S14 BT. Ascend 25 ft. over SE. slope. |
| 21.00 | Spur, slopes N. 75° E.; desc. 270 ft. over N. slope, changing to NE. slope. |
| 28.30 | Ravine, course NE.; ascend 30 ft. over SE. slope. |
| 29.95 | Top of ascent on E. slope; desc. 120 ft. over NE. slope. |
| 33.35 | Ravine, course N. 85° E.; asc. 45 ft. over SE. slope. |
| 35.50 | Spur, slopes E.; desc. 60 ft. over NE. slope. |
| 38.20 | Ravine, course E.; asc. 25 ft. over SE. slope. |
| 39.00 | Small spur, slopes N. 85° E.; desc. 30 ft. over NE. slope. |
| 40.00 | Point for the ¼ sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap marked <div style="text-align: center;"> T21S R11W ¼ S 14 S 13 1957 </div> from which A fir, 58 ins. diam., bears S. 28° E., 54 lks. dist., marked ¼ S13 BT. A fir, 62 ins. diam., bears S. 19½° W., 47 lks. dist., marked ¼ S14 BT. Descend 300 ft. over broken NE. slope, through burned timber and undergrowth, in logged area. |
| 51.60 | Floor of narrow canyon, at end of point of spur from S. 5° W.; edge bears SE. and SW.; desc. slightly over floor of canyon. |
| 52.00 | Dry bed of stream, 6 lks. wide, course N. 5° W.; desc. 60 ft. along bottom. |