

County Surveyor's Record, Douglas County, Oregon

7

Survey of the East and West Center Line of Sec. 13, T. 21 S., R. 11 W.

CHAINS

Beginning at the $\frac{1}{4}$ sec. cor. of sec. 13 only, on the E. bdy. of the Tp., which is monumented with an iron pipe, 1 in. diam., 6 ins. above ground, firmly set, from which

A dead fir, 20 ins. diam., bears N. 65° W., 6 lks. dist., with partial scribe marks visible on nearly healed blaze.

A hemlock, 12 ins. diam., bears S. 70° W., 12 lks. dist., with partial scribe marks visible on opened blaze.

Build a mound of stone, $2\frac{1}{2}$ ft. base, to top of iron post, and mark a new bearing tree, as follows:

A hemlock, 10 ins. diam., bears N. $2\frac{3}{4}$ ° W., 48 lks. dist., marked $\frac{1}{4}$ S13 BT.

N. 85° 36' W., along the E. and W. center line of sec. 13.

4.00 Desc. 200 ft. over steep W. slope, through dense undergrowth. Ravine, course S. 35° W.; asc. 20 ft. along S. slope.

7.00 Spur, slopes S. 10° W.; desc. 210 ft. over SW. slope.

13.80 Unimproved road, bears NW. and SE.

14.00 Dry bed of stream, 10 lks. wide, course NW.; asc. 20 ft. over NE. slope.

15.30 Point of spur, slopes N. 10° E.; desc. 20 ft. over NW. slope.

17.00 Unimproved road, bears N. 58° E. and S. 58° W.

17.30 Dry bed of stream, 10 lks. wide, course N. 60° E.; asc. 320 ft. over broken SE. slope, changing to broken S. slope.

40.10 Set a vine maple post, 5 ft. long, $2\frac{1}{2}$ ins. square, driven 18 ins. in the ground to mark line. Descend 20 ft. over SW. slope, through heavy timber and dense undergrowth, partly burned.

41.30 Head of ravine, course S.; desc. slightly along broken S. slope.

44.90 Ravine, course S. 30° E.; asc. 150 ft. over E. slope.

47.80 Spur, slopes S. 30° E.; desc. 130 ft. over SW. slope.

52.35 Ravine, course S. 25° E.; asc. 300 ft. over NE. slope.

58.60 Ridge, the divide bet. Murphy Creek and Cassidy Creek, bears N. 5° E. and S. 5° W.; desc. 50 ft. over NW. slope, through cleanly burned area.

60.15 Set a wooden post, $4\frac{1}{2}$ ft. long, 3 ins. square, driven 18 ins. in the ground to mark line. Descend 5 ft. along N. slope.

60.70 Spur, slopes N. 30° W.; desc. 355 ft. over steep W. slope.

67.05 Dry bed of stream, 2 lks. wide, course N. 40° W.; asc. 75 ft. over NE. slope.

71.80 Spur, slopes NW.; desc. 220 ft. over W. slope.

75.95 Dry bed of stream, 5 lks. wide, course N.; asc. 200 ft. over E. slope, changing to NE. slope.

80.20 The $\frac{1}{4}$ sec. cor. of secs. 13 and 14.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, maple, and alder, mostly logged or burned.