

Dependent Resurvey of a Portion of the East Boundary of T. 20 S., R. 8 W.

CHAINS

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

T 20 S	T 20 S	
S 13	S 18	CC
	S 19	
R 8 W	R 7 W	
1954		

from which new bearing trees

A fir, 52 ins. diam., bears N. $58\frac{1}{2}^\circ$ E., 120 lks. dist., marked T20S R7W S18 CC BT.

A maple, 14 ins. diam., bears S. 87° E., 84 lks. dist., marked T20S R7W S19 CC BT.

The corner falls on top of ascent on W. slope.

Descend 16 ft. over NW. slope.

18.63 Branch, 3 lks. wide, course N. 80° W.; asc. 227 ft. over SW. slope.

24.65 Spur, slopes N. 85° W.; desc. 246 ft. over broken NW. slope.

38.85 The $\frac{1}{4}$ sec. cor. of sec. 13, determined at record distance from the original bearing trees:

A fir, 60 ins. diam., bears N. 12° E., 25 lks. dist., marked $\frac{1}{4}$ S BT on bark.

A fir, 66 ins. diam., bears N. 73° W., 28 lks. dist., partial marks visible on bark. (Record bearing N. 67° W.)

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

$\frac{1}{4}$ S 13	
1954	

from which a new bearing tree

A fir, 58 ins. diam., bears S. 89° W., 37 lks. dist., marked $\frac{1}{4}$ S13 BT.

N. $1^\circ 09'$ E., beginning new measurement.

Descend 103 ft. over NW. slope.

2.74 Branch, 3 lks. wide, course S. 80° W.; asc. 208 ft. over SE. slope.

12.22 Top of ascent on E. slope; desc. 4 ft. along E. slope.

15.12 Wet ravine, drains S. 50° E.; asc. 253 ft. over S. slope.

19.44 A fir snag, 38 ins. diam., bears W., 10 lks. dist., bark scribed $\frac{1}{4}$ S on east side, apparently marked for the $\frac{1}{4}$ sec. cor. of sec. 18, from which:

A fir snag, 30 ins. diam., bears NE., 12 lks. dist., bark scribed BT $\frac{1}{4}$.