

County Surveyor's Record, ⁶Douglas County, Oregon

Dependent Resurvey of a Portion of the East Boundary of T. 20 S., R. 8 W.

CHAINS

A fir snag, 34 ins. diam., bears S. 33° E., 10 lks. dist., with partial scribe marks visible on scaled bark blaze.

A fir, 28 ins. diam., bears S. 87° W., 31 lks. dist., plainly blazed and healed. (Record calls for a dogwood, 7 ins. diam.)

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

T 20 S	T 20 S	
S 12	S 7	CC
R 8 W	S 18	R 7 W
		1954

from which a new bearing tree

A hemlock, 8 ins. diam., bears N. 39 $\frac{3}{4}$ ° E., 27 lks. dist., marked T20S R7W S7 CC BT.

Ascend 43 ft. over SE. slope.

- 22.48 Head of ravine, drains S. 80° E.; asc. 87 ft. over S. slope.
- 25.72 Spur ridge, bears N. 50° E. and S. 50° W.; desc. 170 ft. over NW. slope.
- 33.04 Bottom of descent on W. slope; asc. 20 ft. along W. slope.
- 34.82 Spur, slopes N. 60° W.; desc. 232 ft. over N. slope.
- 39.25 Branch, 1 lk. wide, bears N. 60° W.; asc. 26 ft. over SW. slope.
- 40.03 The $\frac{1}{4}$ sec. cor. of sec. 12, determined at record bearing from the original bearing trees:

A fir, 20 ins. diam., bears S. 65° E., 15 lks. dist., with marks BT remaining on bark. (Record distance, 13 lks.)

A fir, 50 ins. diam., bears S. 52° W., 10 lks. dist., with marks BT $\frac{1}{4}$ S remaining on bark. (Record distance, 7 lks.)

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

$\frac{1}{4}$ S 12	
	1954

from which a new bearing tree

A fir, 60 ins. diam., bears N. 51 $\frac{1}{2}$ ° W., 70 lks. dist., marked $\frac{1}{4}$ S12 BT.

N. 1° 02' E., beginning new measurement.

Ascend 26 ft. over SW. slope.

- 1.67 Spur, slopes N. 70° W.; desc. 127 ft. over NW. slope.
- 5.94 Branch, 4 lks. wide, course S. 60° W.; asc. 140 ft. over SE. slope.
- 9.86 Top of ascent on E. slope; desc. 51 ft. along E. slope.