

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the East Boundary of T. 20 S., R. 8 W.

CHAINS

- 30.31 Ridge dividing Smith River and Siuslaw River, bears S. 80° E. and N. 80° W.; desc. 218 ft. over N. slope.
- 34.70 Ravine, drains N. 60° E.; asc. 122 ft. over SE. slope.
- 39.57 Point for the $\frac{1}{4}$ sec. cor. of sec. 1, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap marked
- $$\frac{1}{4} \text{ S } 1 \left| \right.$$

1954
- from which
- A fir, 10 ins. diam., bears N. 19° W., 24 lks. dist., marked $\frac{1}{4}$ S1 BT.
- A fir, 10 ins. diam., bears S. 47° W., 31 lks. dist., marked $\frac{1}{4}$ S1 BT.
- Ascend 8 ft. over SE. slope.
- 41.00 Spur, slopes NE.; desc. 467 ft. over NW. slope.
- 52.00 Dry branch, 5 lks. wide, course N. 50° E.; asc. 98 ft. over SE. slope.
- 54.90 Top of ascent on E. slope; desc. 152 ft. along E. slope.
- 62.00 Enter creek bottom land, bears N. and S. 10° E.; desc. 16 ft. along bottom near W. side of creek.
- 65.00 Creek, 5 lks. wide, course N. 30° W.; asc. 77 ft. along W. slope.
- 71.65 Spur, slopes N. 70° W.; desc. 90 ft. over NW. slope.
- 75.10 Esmond Creek, 5 lks. wide, course S. 70° W.; asc. 38 ft. over SE. slope.
- 78.25 Ravine, drains S. 30° E.; asc. 65 ft. over SW. slope.
- 79.14 The cor. of Tps. 19 and 20 S., R. 8 W., monumented with an iron post, 3 ins. diam., 8 ins. above ground, marked and witnessed as described in the official record.

Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, cedar, maple, alder, chinquapin, dogwood, madrona, and cascara. Undergrowth, vine maple, hazel, huckleberry, slickleaf, arrowwood, and salal.

Dependent Resurvey, Portion of the West Boundary of T. 20 S., R. 8 W.
(Restoring the 1883 survey by William P. Wright)

From the cor. of secs. 19 and 30, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., 8 ins. above ground, firmly set, marked and witnessed as described in the official record.

N. 0° 42' E., along the W. bdy. of sec. 19, marking and blazing the true line.

Ascend 10 ft. along W. slope, through heavy timber and dense undergrowth.