

Dependent Resurvey of a Portion of the West Boundary of T. 20 S., R. 8 W.

CHAINS

A cedar, 36 ins. diam., bears N. 47° W., 65 lks. dist., with marks T S13 T20 R9W visible on partly healed blaze.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

| | |
|--------|--------|
| T 20 S | T 20 S |
| R 9 W | S 18 |
| S 24 | S 19 |
| | R 8 W |
| | 1954 |

from which a new bearing tree

A hemlock, 28 ins. diam., bears S. 10° E., 100 lks. dist., marked T20S R8W S19 BT.

Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, maple, cedar, alder, chinquapin, dogwood, madrona, and cascara. Undergrowth, vine maple, hazel, huckleberry, slickleaf, arrowwood, and salal.

N. 0° 47' E., along the W. bdy. of sec. 18.

Descend 20 ft. over NW. slope, through heavy timber and dense undergrowth.

- 0.63 Wet ravine, drains NE.; desc. 11 ft. along E. slope.
 - 4.12 Spur, slopes N. 60° E.; desc. 204 ft. over NE. slope.
 - 8.03 Branch, 1 lk. wide, course E.; asc. 167 ft. over SE. slope.
 - 12.10 Spur, slopes E.; desc. 279 ft. over N. slope.
 - 21.52 Branch, 5 lks. wide, course SE.; asc. 271 ft. over SW. slope.
 - 32.55 Top of ascent, slopes W.; desc. 27 ft. along W. slope.
 - 34.41 Ravine, drains S. 70° W.; asc. 133 ft. over S. slope.
 - 37.46 Point for the closing cor. of secs. 13 and 24, T. 20 S., R. 9 W., at proportionate distance.
- Ascend 51 ft. over S. slope.
- 38.82 The $\frac{1}{4}$ sec. cor. of sec. 18, determined at record bearing and distance from the original bearing trees:

A turned out fir, 16 ins. diam., bears N. 71° W., 10 lks. dist., marked with a rotted blaze.

A fir snag, 24 ins. diam., bears S. 70° E., 15 lks. dist., marked BT $\frac{1}{4}$ S on bark.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

| |
|--------------------|
| $\frac{1}{4}$ S 18 |
| 1954 |

from which