

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 8 W.

CHAINS

A fir, 15 ins. diam., bears S. 30° W., 42 lks. dist.,
marked T20S R8W S15 BT.

A fir, 15 ins. diam., bears N. 68½° W., 38 lks. dist.,
marked T20S R8W S10 BT.

Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, maple, cedar, alder, chinquapin, dogwood, madrona, and cascara. Undergrowth, vine maple, hazel, huckleberry, slickleaf, arrowwood, and salal.

From the cor. of secs. 11, 12, 13, and 14.

N. 88° 38' W., bet. secs. 11 and 14.

Descend 242 ft. over SW. slope, through heavy timber and dense undergrowth.

- 6.09 Wet ravine, course S. 5° W.; asc. 37 ft. over SE. slope.
- 7.14 Spur, slopes S. 5° W.; desc. 37 ft. over SW. slope.
- 9.66 Branch, 5 lks. wide, course S. 55° E.; asc. 179 ft. over NE. slope.
- 15.49 Spur, slopes NE.; asc. 41 ft. along N. slope.
- 20.69 Wet ravine, course N. 60° E.; asc. 314 ft. over SE. slope.
- 27.99 Ridge dividing N. Sister Creek and S. Sister Creek, bears N. 30° E. and S. 30° W.; desc. 202 ft. over NW. slope.
- 32.54 Spur, slopes N. 50° W.; desc. 35 ft. over SW. slope.
- 33.99 Ravine, drains N.; asc. 216 ft. over NE. slope.
- 39.645 Point for the ¼ sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

$$\frac{1}{4} \begin{array}{l} S 11 \\ S 14 \end{array}$$

1954

from which

A fir, 17 ins. diam., bears N. 43¼° W., 17 lks. dist.,
marked ¼ S11 BT.

A fir, 13 ins. diam., bears S. 57° W., 54 lks. dist.,
marked ¼ S14 BT.

Ascend 7 ft. over NE. slope.

- 41.84 Ridge, bears N. 70° E. and S. 70° W.; desc. 28 ft. over NW. slope.
- 44.68 Same ridge, bears S. 55° E. and W.; desc. 47 ft. along top of ridge.
- 47.52 Leave ridge, bears S. 60° W.; desc. 43 ft. along N. slope.
- 52.67 Spur, slopes N. 25° W.; desc. 305 ft. over NW. slope, changing to W. slope.
- 58.98 Ravine, drains N. 40° W.; asc. 83 ft. over NE. slope.