


Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 8 W.

CHAINS

- 13.75 Branch, 1 lk. wide, course S. 65° W.; asc. 150 ft. over S. slope, changing to SW. slope.
- 22.35 Spur, slopes N. 80° W.; desc. 85 ft. over NW. slope.
- 26.33 Branch, 1 lk. wide, course W.; asc. 34 ft. along W. slope.
- 27.62 Branch, 1 lk. wide, course SW.; asc. 148 ft. over S. slope, changing to broken W. slope.
- 39.28 Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked



from which

A fir, 50 ins. diam., bears S. 8° E., $4\frac{1}{2}$ lks. dist., marked $\frac{1}{4}$ S15 BT.

A hemlock, 11 ins. diam., bears N. 44° W., 9 lks. dist., marked $\frac{1}{4}$ S16 BT.

Ascend 12 ft. along W. slope.

- 43.27 Ridge, dividing N. Sister Creek and S. Sister Creek, bears E. and W.; desc. 551 ft. over NE. slope, changing to N. slope.
- 62.25 North Sister Creek, 40 lks. wide, course S. 80° W.; asc. 397 ft. over general S. slope.

78.56 The cor. of secs. 9, 10, 15, and 16, determined from the original bearing trees as follows:

A rotted fir stump, 24 ins. diam., bears N. 57° E., 29 lks. dist., with no marks remaining. (Record distance, 27 lks.)


A fir snag, 30 ins. diam., bears S. 34° E., 31 lks. dist., marked BT S15 T20S R8W. (Record bearing, S. 31° E.)

A fir, 50 ins. diam., bears S. 80° W., 49 lks. dist., marked BT S16 T20S R8W on bark. (Record distance, 47 lks.)

A fir, 50 ins. diam., bears N. 36° W., 35 lks. dist., marked BT S9 T20S R8W on bark. (Record distance, 32 lks.)

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked



from which new bearing trees

A hemlock, 13 ins. diam., bears N. 78° E., 12 lks. dist., marked T20S R8W S10 BT.