


Dependent Resurvey of Portion of Subdivisional Lines of T. 20 S., R. 8 W.

CHAINS

- 26.85 Spur, slopes S. 75° E.; desc. 64 ft. over NE. slope.
- 31.90 Ravine, drains S. 70° E.; asc. 154 ft. over SE. slope.
- 37.515 Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked




from which

A hemlock, 14 ins. diam., bears N. 7 $\frac{1}{2}$ ° W., 25 lks. dist., marked $\frac{1}{4}$ S9 BT.

A hemlock, 6 ins. diam., bears S. 71 $\frac{1}{2}$ ° E., 4 lks. dist., marked $\frac{1}{4}$ S10 BT.

Ascend 102 ft. over SE. slope, changing to E. slope.

- 41.95 Top of ascent on E. slope; desc. 107 ft. over NE. slope.
- 45.00 Branch, 1 lk. wide, course S. 80° E.; asc. 170 ft. over S. slope.
- 52.40 Ridge, bears N. 70° E. and S. 80° W.; desc. 472 ft. over NW. slope.
- 67.00 Ravine, drains W.; asc. 84 ft. over broken SW. slope.
- 70.70 Top of ascent on W. slope; desc. 83 ft. over NW. slope.
- 73.00 Ravine, drains N. 85° W.; asc. 26 ft. over S. slope, changing to W. slope.
- 75.03 Point for the cor. of secs. 3, 4, 9, and 10, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked



from which

A fir, 50 ins. diam., bears N. 47 $\frac{1}{2}$ ° E., 51 lks. dist., marked T20S R8W S3 BT.

A fir, 32 ins. diam., bears S. 78 $\frac{1}{2}$ ° E., 51 lks. dist., marked T20S R8W S10 BT.

A fir, 60 ins. diam., bears S. 33° W., 111 lks. dist., marked T20S R8W S9 BT.

A fir, 50 ins. diam., bears N. 77° W., 60 lks. dist., marked T20S R8W S4 BT.

Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, maple, cedar, alder, chinquapin, dogwood, madrona, and cascara. Undergrowth, vine maple, hazel, huckleberry, slickleaf, arrowwood, and salal.