

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 8 W.

CHAINS

From the cor. of secs. 2, 3, 10, and 11.

N. 88° 46' W., bet. secs. 3 and 10.

Descend 84 ft. over W. slope, through heavy timber and dense undergrowth.

3.20 Ravine, drains S. 65° W.; asc. 85 ft. over SE. slope.

9.75 Spur, slopes SE.; desc. 100 ft. over SW. slope.

13.00 Ravine, drains S. 60° W.; asc. 58 ft. over SE. slope.

14.95 Top of ascent on S. slope; desc. 54 ft. over SW. slope.

17.80 Ravine, drains S. 75° E.; asc. 288 ft. over E. slope.

24.25 Spur, slopes S. 10° W.; desc. 371 ft. over SW. slope.

34.65 Branch, 2 lks. wide, course S. 10° W.; asc. 110 ft. over SE. slope.

39.97 Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

$\frac{1}{4}$ S 3
S 10

1954

from which

A maple, 24 ins. diam., bears N. 79° E., 37 lks. dist., marked $\frac{1}{4}$ S3 BT.

A maple, 15 ins. diam., bears S. 73° W., 48 lks. dist., marked $\frac{1}{4}$ S10 BT.

Ascend 287 ft. over SE. slope.

48.40 Spur, slopes S. 15° W.; desc. 90 ft. over broken SW. slope, changing to S. slope.

56.70 Ridge, bears N. 30° E. and S. 30° W.; desc. 307 ft. over NW. slope.

66.80 Ravine, drains N. 15° W.; asc. 213 ft. over NE. slope.

71.50 Spur, slopes N.; desc. 372 ft. over W. slope.

79.94 The cor. of secs. 3, 4, 9, and 10.

Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, maple, cedar, alder, chinquapin, dogwood, madrona, and cascara. Undergrowth, vine maple, hazel, huckleberry, slickleaf, arrowwood, and salal.

N. 2° 44' E., bet. secs. 3 and 4.

Ascend 119 ft. along W. slope, through heavy timber and dense undergrowth.

3.85 Spur, slopes N. 75° W.; desc. 399 ft. over broken NW. slope.

18.25 Branch, 5 lks. wide, course S. 60° W.; asc. 501 ft. over SE. slope.