

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 8 W.

CHAINS

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 8 \text{ | S } 9 \\ | \\ 1954 \end{array}$$

from which new bearing trees

A hemlock, 35 ins. diam., bears S. $22\frac{1}{4}^{\circ}$ E., 79 lks. dist., marked $\frac{1}{4}$ S9 BT.A fir, 40 ins. diam., bears N. 11° W., 76 lks. dist., marked $\frac{1}{4}$ S8 BT.N. $3^{\circ} 26'$ W., beginning new measurement.

Ascend 101 ft. over SE. slope.

7.05 Top of ascent on E. slope; desc. 54 ft. over NE. slope.

9.25 Branch, 1 lk. wide, course S. 85° E.; asc. 178 ft. over S. slope.

16.18 Top of ascent on E. slope; desc. 104 ft. along E. slope.

26.50 Branch, 2 lks. wide, course S. 8° E.; asc. 454 ft. over broken SW. slope.

36.74 The cor. of secs. 4, 5, 8 and 9, determined at record bearing and distance from the original bearing trees:

A fir, turned out, 19 ins. diam., bears N. 63° E., 26 lks. dist., marked BT S4 T2OS R8 W.A fir, 22 ins. diam., bears S. 65° E., 33 lks. dist., marked with a healed blaze.A fir, turned out, 40 ins. diam., bears S. 35° W., 10 lks. dist., marked with a healed blaze.A fir, 24 ins. diam., turned out, bears N. 70° W., 17 lks. dist., marked BT S5 T2OS R8W.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

$$\begin{array}{c} \text{T2OS R8W} \\ \text{S } 5 \text{ | S } 4 \\ \text{S } 8 \text{ | S } 9 \\ 1954 \end{array}$$

from which new bearing trees

A fir, 23 ins. diam., bears N. 69° E., 48 lks. dist., marked T2OS R8W S4 BT.A fir, 39 ins. diam., bears S. $13\frac{1}{4}^{\circ}$ W., 37 lks. dist., marked T2OS R8W S8 BT.A fir, 28 ins. diam., bears N. $31\frac{1}{2}^{\circ}$ W., 57 lks. dist., marked T2OS R8W S5 BT.