

## County Surveyor's Record, Douglas County, Oregon

43

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 8 W.

CHAINS	
	From the cor. of secs. 19, 20, 29, and 30, monumented with an iron post, 2 ins. diam., 8 ins. above ground, firmly set, marked and witnessed as described in the official record.
	N. 0° 15' E., bet. secs. 19 and 20.
	Ascend 22 ft. over SE. slope, through heavy timber and dense undergrowth.
0.84	Ridge, bears N. 70° W. and S. 60° E.; desc. 413 ft. over broken NE. slope.
10.73	Branch, 8 lks. wide, course N. 60° E.; asc. 440 ft. over broken S. slope.
22.38	Ridge, bears E. and W.; desc. 404 ft. over N. slope, changing to NE. slope.
35.64	Branch, 3 lks. wide, course N. 40° E.; desc. 3 ft. over broken NE. slope.
38.35	The $\frac{1}{4}$ sec. cor. of secs. 19 and 20, determined from the original bearing trees:
	A cedar, 62 ins. diam., bears S. 53° E., 42 lks. dist., marked with a rotted blaze. (Record distance, 34 lks.)
	A fir snag, 85 ins. diam., bears N. 60° W., 47 lks. dist., with marks BT $\frac{1}{4}$ S remaining on bark.
	At the corner point
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked.
	from which new bearing trees
	A hemlock, 28 ins. diam., bears N. 82 $\frac{3}{4}$ ° E., 83 lks. dist., marked $\frac{1}{4}$ S20 BT.
	A fir, 25 ins. diam., bears N. 81 $\frac{1}{2}$ ° W., 51 lks. dist., marked $\frac{1}{4}$ S19 BT.
	N. 0° 07' W., beginning new measurement.
	Descend 181 ft. over broken NE. slope.
15.10	Smith River, 40 lks. wide, course N. 60° W.; asc. 66 ft. over SW. slope.
18.84	Top of ascent on W. slope; desc. 68 ft. over NW. slope.
26.90	Smith River, 40 lks. wide, course NE.; asc. 328 ft. over SE. slope.
38.45	Spur, slopes S. 30° E.; desc. 47 ft. along E. slope.
40.01	The cor. of secs. 17, 18, 19 and 20, determined from the original bearing trees:
	A fir snag, 28 ins. diam., bears N. 63° E., 70 lks. dist., marked with a healed blaze.
	A fir snag, 47 ins. diam., bears S. 77 $\frac{1}{2}$ ° E., 19 lks. dist., marked with a healed blaze. (Record bearing, S. 79° E.)
	A fir snag, 57 ins. diam., bears S. 70° W., 54 lks. dist., with