

## County Surveyor's Record, Douglas County, Oregon

44

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 8 W.

CHAINS

marks BT 19 remaining on bark. (Record distance, 56 lks.)

A fir, 62 ins. diam., bears N. 76° W., 43 lks. dist., with marks S 8 W remaining on bark. (Record distance, 42 lks.)

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

$$\begin{array}{r} \text{T20S R8W} \\ \text{S 18 | S 17} \\ \text{S 19 | S 20} \\ \hline 1954 \end{array}$$

from which new bearing trees

A fir, 45 ins. diam., bears N. 79½° E., 115 lks. dist., marked T20S R8W S17 BT.

A hemlock, 18 ins. diam., bears S. 12¼° E., 34 lks. dist., marked T20S R8W S20 BT.

A fir, 52 ins. diam., bears S. 49½° W., 80 lks. dist., marked T20S R8W S19 BT.

Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, maple, cedar, alder, chinquapin, dogwood, madrona, and cascara. Undergrowth, vine maple, hazel, huckleberry, slickleaf, arrowwood, and salal.

From the cor. of secs. 16, 17, 20 and 21.

S. 88° 39' W., bet. secs. 17 and 20.

Ascend 232 ft. along N. slope, changing to NE. slope, through heavy timber and dense undergrowth.

- 14.25 Spur ridge, bears N. 10° E. and S. 10° W.; desc. 91 ft. over NW. slope.
- 21.50 Branch, 1 lk. wide, course N.; asc. 44 ft. over NE. slope
- 24.00 Spur, slopes N. 20° E.; desc. 43 ft. over NW. slope.
- 26.10 Branch, 2 lks. wide, course N. 25° E.; asc. 67 ft. over NE. slope.
- 30.50 Spur ridge, bears N. 30° E. and S. 30° W.; desc. 89 ft. over NW. slope.
- 38.50 Branch, 2 lks. wide, course N.; asc. 53 ft. over NE. slope.
- 39.88 Point for ¼ sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked
- $$\begin{array}{r} \text{S 17} \\ \frac{1}{4} \text{ S 20} \\ \hline 1954 \end{array}$$
- from which
- A fir, 48 ins. diam., bears N. 30° W., 45 lks. dist., marked ¼ S17 BT.
- A fir, 42 ins. diam., bears S. 28° W., 27 lks. dist., marked ¼ S20 BT.
- Corner falls on top of ascent on N. slope.