

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 8 W.

CHAINS 10.96	Ridge, bears N. and S.; desc. 451 ft. over NW. slope.
22.19	Branch, 15 lks. wide, course S. 15° W.; asc. 385 ft. over SE. slope.
37.61	Top of ascent on S. slope; desc. 5 ft. over SW. slope.
39.49	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked FOOK PER ROBERTS DEC 86 M103-36 $\frac{1}{4}$ S 7 S 18 1954
	from which A hemlock, 13 ins. diam., bears N. 15° E., 29 lks. dist., marked $\frac{1}{4}$ S7 BT. A hemlock, 20 ins. diam., bears S. 60 $\frac{1}{4}$ ° E., 38 lks. dist., marked $\frac{1}{4}$ S18 BT.
	Descend 297 ft. over SW. slope.
63.49	Branch, 4 lks. wide, course S. 60° E.; asc. 397 ft. over NE. slope, changing to SE. slope.
97.24	The cor. of secs. 7 and 18 on the W. bdy. of the Tp. Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, maple, cedar, alder, chinquapin, dogwood, madrona, and cascara. Undergrowth, vine maple, hazel, huckleberry, slickleaf, arrowwood, and salal.
	From the cor. of secs. 7, 8, 17 and 18. N. 1° 20' W., bet. secs. 7 and 8. Ascend 155 ft. along broken E. slope, through heavy timber and dense undergrowth.
5.25	Bluff, bears E. and W.; desc. 125 ft. over steep N. slope.
9.94	Dry branch, 3 lks. wide, course S. 70° E.; asc. 303 ft. along broken E. slope.
23.23	Ridge, bears N. 60° E. and S. 60° W.; desc. 120 ft. over N. slope.
25.36	Ravine, drains W.; asc. 255 ft. over S. slope.
32.67	Top of ascent on SW. slope; desc. 301 ft. over NW. slope.
39.91	The $\frac{1}{4}$ sec. cor. of secs. 7 and 8, determined at record bearing and distance from the original bearing trees: A cedar, 24 ins. diam., bears N. 55° E., 29 lks. dist., with marks BT $\frac{1}{4}$ S visible on partially healed blaze. A cedar, 48 ins. diam., bears S. 60° W., 42 lks. dist., marked with a healed blaze. At the corner point Set an iron post, 10 ins. long, 1 in. diam., 8 ins. in solid rock, with brass cap marked $\frac{1}{4}$ S 7 S 8 1954