

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 25 S., R. 7 W.

CHAINS

Remark the original corner tree, $\frac{1}{4}$ S10 on W. face, and S11 on the E. face.

from which new bearing trees,

A fir, 22 ins. diam., bears S. $17\frac{1}{2}^\circ$ E., 76 lks. dist., mkd. $\frac{1}{4}$ S11 BT.

A fir, 6 ins. diam., bears S. 74° W., 24 lks. dist., mkd. $\frac{1}{4}$ S10 BT.


N. $0^\circ 12'$ E., beginning new measurement.

Ascend 344 ft. over SE. slope changing to S. slope over rock bluff, through scattering timber.

15.60 Spur, slopes SW.; asc. 12 ft. along W. slope.

20.13 Point for the N 1/16 sec. cor. of secs. 10 and 11.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



from which

A white fir, 9 ins. diam., bears N. $69\frac{1}{2}^\circ$ E., $51\frac{1}{2}$ lks. dist., mkd. N 1/16 S11 BT.

A white fir, 8 ins. diam., bears S. $14\frac{1}{2}^\circ$ W., 94 lks. dist., mkd. N 1/16 S10 BT.

Descend 29 ft. over NW slope, enter logged area, edge bears E. and W., bending to S.

21.99 Abandoned skid road, 15 lks. wide, bears N. 10° E. and S. 10° W.


25.66 Ravine, course SW., also skid road, 15 lks. wide, bears NE. and S. 30° W.; asc. 61 ft. over S. slope.

29.18 Creek, 2 lks. wide, course S. curving to SW.; asc. 198 ft. over S. slope.

34.55 Dirt access road, 20 lks. wide, bears E. and W.

40.26 Point for the cor. of secs. 2, 3, 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

A white fir, 24 ins. diam., bears N. $39\frac{1}{2}^\circ$ E., 31 lks. dist., mkd. T25S R7W S2 BT.

A white fir, 18 ins. diam., bears S. 10° E., 9 lks. dist., mkd. T25S R7W S10 BT.

A white fir, 15 ins. diam., bears S. 56° W., $58\frac{1}{2}$ lks. dist.,