

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 25 S., R. 7 W.

CHAINS

mkd. T25S R7W S10 BT.

A white fir, 23 ins. diam., bears N. 54° W., 108 lks. dist.,
mkd. T25S R7W S3 BT.Land, mountainous. Soil, rocky loam, and rock bluff in N. half,
sandstone outcroppings in S. half mile. Timber, fir, cedar, yew,
madrone, and white oak; undergrowth, hazel, ocean spray, poison oak,
blackberry, gooseberry, fern, and salal.From the cor. of secs. 1, 2, 11 and 12, which has been perpetuated
and recorded, by J. W. Byron, D. C. S., in 1958, at record dist. from
three original bearing trees. Monumented with a very old wooden
stake, 4x4 ins., cross section 3 ft. long, with scribe marks S1 and
other illegible markings on it (possible original), firmly set along-
side an iron post, 1 in. diam., firmly set, 8 ins. above ground, with
brass cap mkd., COUNTY SURVEYORS OFFICE T25S R7W S1 S2 S11 S12 1957.

from which original bearing trees:

A cedar, 40 ins. diam., bears N. 14° E., 130 lks. dist., with
the overgrowth of scribe marks tacked to the tree. (Record bear-
ing N. 30° E.)A fir, 56 ins. diam., bears S. 33½° E., 72 lks. dist., bark
scribed T25S S1 BT. (Record bearing S. 53° E.)A cedar, 48 ins. diam., bears N. 34° W., 33 lks. dist., with
scribe marks T25S R7W S2 visible on opened blaze. The tree has
been re-scribed by the county surveyor T25S R7W S2 CS. BT.

and county surveyor's bearing trees:

A cedar, 13 ins. diam., bears N. 13° E., 44 lks. dist., mkd.
T25S R7W S1 CS BT.A cedar, 15 ins. diam., bears S. 65° E., 7½ lks. dist., mkd.
T25S R7W S12 CS BT.A cedar, 11 ins. diam., bears S. 44° W., 109 lks. dist., mkd.,
CS S11 T25S R7W BT.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground,
with brass cap mkd.

T25S R7W
S 2 S 1
S11 S 12
.1958

Deposit local cor. material alongside iron post.

S. 88° 25' W., bet. secs. 2 and 11.

Ascend 69 ft. over NE. slope, through scattering timber and undergrow-
th along the south edge of logged area.

6.95 Top of ascent, slopes N.; desc. 227 ft. over broken NW. slope.

39.79 The ¼ sec. cor. of secs. 2 and 11, determined at record distance
from two original bearing trees, as follows:A fir snag, 24 ins. diam., bears N. 18½° E., 77 lks. dist.,
bark scribed S½ BT. (Record bearing N. 12° W.)A sawed cedar stump, 36 ins. diam., bears S. 54½° W., 29 lks.
dist., with portion of scribe mark B visible on opened blaze,