

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 25 S., R. 7 W.

CHAINS

SE. curving to E.

40.28 Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T25S R7W

$$\begin{array}{c} \uparrow \\ \frac{1}{4} \\ \text{S } 3 \text{ S } 2 \end{array}$$

1958

from which

A fir, 9 ins. diam., bears N. 39° E., $96\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S2 BT.A hemlock, 17 ins. diam., bears S. 66° W., $98\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S3 BT.

Ascend 68 ft. over SE. slope changing to E. slope. along W. edge of logged area.

46.65 Top of ascent, slopes E.; desc. 510 ft. along E. slope changing to NE. slope.

73.55 Dirt logging road, 20 lks. wide, bears E. and W.

76.75 Skid road, 10 lks. wide, bears E. and W.

80.10 Skid road, 15 lks. wide, bears N. 70° W. and S. 70° E.

82.40 The cor. of secs. 2, 3, 34 and 35, on N. bdy. of Tp., which is determined at the intersection of the bearings from the faces of two bearing trees, which do not match the record, but the bark scribing on these trees is of the same character as that used throughout the Tp. and has the same appearance of scribing established at the same date. This same point has been monumented with a wooden stake, 2x2 ins. cross section, 3 ft. above ground, firmly set. Also there is a very old squared, wooden stake 4x4 ins. cross section lying at this point, no scribe marks visible. I accept this position as the best available evidence of the original cor.

from which

A fir, 36 ins. diam., bears S. 66° E., 75 lks. dist., bark scribed T2 R W S BT and other illegible scribe marks.A fir, 36 ins. diam., bears S. 35° W., $71\frac{1}{2}$ lks. dist., bark scribed T25S R7W S BT, the scribing has been separated by a bark split.

and a locally established bearing tree of which I have no record:

A cedar, 25 ins. diam., bears S. 71° E., $65\frac{1}{2}$ lks. dist., with scribe marks T W 2 BT. visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.
$$\begin{array}{c} \text{T25S R7W} \\ \text{S } 34 \text{ S } 35 \\ \hline \text{S } 3 \text{ S } 2 \end{array}$$
T25S
1958

from which