

County Surveyor's Record, Douglas County, Oregon

7

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 25 S., R. 7 W.

CHAINS

A cedar, 6 ins. diam., bears N. $45\frac{1}{2}^{\circ}$ E., 54 lks. dist., mkd. T24S R7W S35 BT.

A fir, 20 ins. diam., bears N. $71\frac{1}{2}^{\circ}$ W., $77\frac{1}{2}$ lks. dist., mkd. T24S R7W S34 BT.

Land, mountainous.

Soil, rocky loam with occasional sandstone outcroppings.

Timber, fir, cedar, hemlock, yew and madrone; undergrowth, ocean spray, gooseberry, fern, salal, blackberry, dogwood, chinquapin, Oregon grape, hazel, willow, and wild rose.

From the cor. of secs. 9, 10, 15 and 16, determined at record distance from two original bearing trees, as follows:

A fir, 53 ins. diam., bears S. 70° W., 42 lks. dist., bark scribed S16 and re-scribed S16 BT by C. Kerr in 1953.

A fir, 49 ins. diam., bears N. 2° W., 60 lks. dist., bark scribed T25S R7W S9 and re-scribed S9 BT by C. Kerr in 1953. (Record bearing N. 5° W.)

and locally established and recorded bearing tree:

A fir snag, 10 ins. diam., bears N. $80\frac{1}{4}^{\circ}$ E., $51\frac{1}{2}$ lks. dist., with scribe marks S15 BT visible on partially healed blaze.

and a bearing tree of which I have no records:

A fir, 40 ins. diam., bears N. $71\frac{1}{4}^{\circ}$ E., $51\frac{1}{2}$ lks. dist., bark scribed T25S R7W S10 BT.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T25S R7W
S 9 S 10
S 16 S 15
1958

from which

A white fir, 12 ins. diam., bears S. $8\frac{1}{4}^{\circ}$ E., 114 lks. dist., mkd. T25S R7W S15 BT.

N. $0^{\circ} 30'$ W., bet. secs. 9 and 10.

Descend 19 ft. over N. slope, through heavy timber and dense undergrowth.

1.245 Left bank of the Umpqua River, bears N. 80° W. and S. 70° E., and point for the meander cor. of secs. 9 and 10, on the left bank of the Umpqua River, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

M C
S 9 S 10
T25S R7W
1958

from which

A hemlock, 24 ins. diam., bears S. $41\frac{1}{2}^{\circ}$ E., 68 lks. dist., mkd. T25S R7W S10 MC BT.