

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 25 S., R. 7 W.

CHAINS

A hemlock, 25 ins. diam., bears S. 84° W., 108 lks. dist.,
mkd. T25S R7W S9 MC BT.

Descend 10 ft. across Umpqua River.

- 8.02 Edge of the right side of the main channel of the Umpqua River,
course N. 70° W.
- 10.548 Point for the meander corner of secs. 9 and 10 on the right side of
the Umpqua River, at proportionate distance; there is no remaining
evidence of the original corner.
- Set a brass tablet, $3\frac{1}{4}$ ins. diam., $3\frac{1}{2}$ ins. stem, in a drilled hole
in exposed bedrock, with top mkd.
- T25S R7W
S 9 | S 10
M C
1958
- from which
- A white oak, 20 ins. diam., bears N. 31 $\frac{1}{2}$ ° E., 130 $\frac{1}{2}$ lks. dist.,
mkd. T25S R7W S10 MC BT.
- A white fir, 15 ins. diam., bears N. 13 $\frac{1}{2}$ ° W., 180 lks. dist.,
mkd. T25S R7W S9 MC BT.
- Ascend 24 ft. over S. slope of river bank.
- 12.65 Top of right bank of Umpqua River, bears N. 70° W. and S. 70° E.;
asc. 391 ft. over S. slope through scattering timber.
- 12.95 Graveled and maintained road, 30 lks. wide, bears N. 70° W. and
S. 70° E.
- 13.25 Four wire transmission line, bears N. 70° W. and S. 70° E.
- 22.80 Top of steep ascent, slopes W.; desc. 27 ft. over NW. slope, through
open prairie, edge bears NW. and SE.
- 28.95 Foot of descent, slopes W.; also graveled and maintained road, 20 lks.
wide, bears E., curving to N. and W., curving to SW.; asc. 15 ft.
along W. slope.
- 36.15 Four wire transmission line, bears E. and W.
- 37.55 Top of ascent, slopes N.; also abandoned logging road, 15 lks. wide,
bears E., curving to N., and W. curving to SW.; enter timber, edge
bears E. and W.; desc. 23 ft. over NW. slope.
- 39.24 Ravine, course W.; asc. 58 ft. over SW. slope.
- 40.81 The $\frac{1}{4}$ sec. cor. of secs. 9 and 10, perpetuated and recorded, by
Byron, D.S.C., in 1958, with an iron pipe, 1 in. diam., 10 ins. above
ground, firmly set, at record bearing and distance from two original
bearing trees, with brass cap mkd. COUNTY SURVEYORS OFFICE T25S R7W
 $\frac{1}{4}$ S9 S10 1957; from which the original bearing trees:
- A white oak snag, 28 ins. diam., bears N. 65° E., 44 lks. dist.,
with the overgrowth of the BT visible on the inside of the
rotted stump.
- A fir, 54 ins. diam., bears S. 75° W., 43 lks. dist., no scribe
marks visible. A large hole at the base of the tree gives ex-
cessive measurement to the diameter.
- and locally established bearing trees:
- A white fir, 12 ins. diam., bears S. 33 $\frac{3}{4}$ ° E., 67 lks. dist.,
mkd. $\frac{1}{4}$ S10 CS BT on a double blaze.