

County Surveyor's Record, Douglas County, Oregon

10

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 25 S., R. 7 W.

CHAINS

Soil, clay loam and sandstone bluffs.
 Timber, fir, cedar, maple, myrtle, yew, white oak, and madrone; undergrowth, hazel, thimbleberry, fern, blackberry, dogwood, willow, ocean spray, wild rose, and poison oak.

From the cor. of secs. 2, 3, 10 and 11.

N. 89° 21' W., between secs. 3 and 10.

Descend 614 ft. over W. slope changing to SW. slope, along N. edge of logged area.

40.17 Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T25S R7W

$\frac{1}{4}$ S 3
 $\frac{1}{4}$ S 10

1958

from which

A cedar, 23 ins. diam., bears North, 10 lks. dist., mkd.
 $\frac{1}{4}$ S3 BT.

A fir, 30 ins. diam., bears S. 63° W., 106 lks. dist., mkd.
 $\frac{1}{4}$ S10 BT.

Descend 626 ft. over W. slope.

78.25 Dirt logging road, 20 lks. wide, course N. 20° E. and SW.

79.60 Creek, 4 lks. wide, course S. 20° W.; asc. 35 ft. over E. slope.

80.34 The cor. of secs. 3, 4, 9 and 10.

Land, mountainous.

Soil, rocky loam with occasional rock outcroppings.

Timber, fir, cedar, hemlock, yew, and madrone; undergrowth, hazel, salal, fern, gooseberry, blackberry, poison oak, and ocean spray.

N. 1° 05' W., between secs. 3 and 4.

Ascend 331 ft. over SE. slope, along E. edge of logged area.

10.84 Abandoned skid road, 15 lks. wide, bears N. 20° E. and S. 20° W.

14.02 Junction of skid roads, 15 lks. wide, extending NE., SW. and N. 10° W.

14.03 Spur, slopes SE.; desc. 54 ft. over NE. slope.

17.72 Skid road, 15 lks. wide, bears N. 10° W. and SE.

23.30 Dry creek bed, 4 lks. wide, course E. curving to S. 20° E.; asc. 64 ft. over S. slope.

25.37 Spur, slopes S. 50° E.; asc. 87 ft. along E. slope.

33.27 Ravine, course S. 10° E.; asc. 181 ft. over S. slope.

40.19 Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground to solid rock, and in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with brass cap mkd.