

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 25 S., R. 7 W.

CHAINS	<p>Timber, fir, cedar, hemlock, yew, madrone, and maple; undergrowth, hazel, fern, salal, dogwood, vinemaple, blackberry, chinquapin, ocean spray, wild rose, Oregon grape, and poison oak.</p>				
	<p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. 89° 41' W., bet. secs. 4 and 9.</p> <p>Ascend 154 ft. over E. slope, along W. edge of logged area.</p>				
10.60	Spur, slopes S.; asc. 55 ft. over SE. slope.				
19.25	Spur, slopes S.; desc. 71 ft. over SW. slope.				
26.90	Creek, 4 lks. wide, course SE.; asc. 329 ft. over E. slope.				
38.10	Spur ridge, bears N. 60° W. and S. 60° E., enter timber, edge bears N. 60° W. and E.; desc. 24 ft. over SW. slope.				
39.74	<p>The $\frac{1}{4}$ sec. cor. of secs. 4 and 9, perpetuated and recorded by J. W. Cole, Deputy County Surveyor, in 1930, from the original bearing trees, monumented with an iron pipe, 1 in. diam., firmly set, 12 ins. above ground, from which the original bearing trees:</p> <p style="padding-left: 40px;">A fir, 65 ins. diam., bears N. 87° W., 200 lks. dist., (196 lks. to the face), re-bark scribed $\frac{1}{4}$ SC BT. (Record distance 195 lks.)</p> <p style="padding-left: 40px;">A madrone, 25 ins. diam., bears S. 88° E., 165 lks. dist., with illegible scribe marks on opened blaze. (Record distance 162 lks.)</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25S R7W</p> <table style="margin: auto;"> <tr> <td style="border: none;">S</td> <td style="border: none;">4</td> </tr> <tr> <td style="border: none;">$\frac{1}{4}$</td> <td style="border: none;">S 9</td> </tr> </table> <p>1958</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears N. $5\frac{3}{4}$° W., $66\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S4 BT.</p> <p style="padding-left: 40px;">A fir, 27 ins. diam., bears S. $18\frac{1}{2}$° E., $33\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S9 BT.</p> <p style="padding-left: 40px;">Deposit county surveyor's iron pipe alongside iron post.</p>	S	4	$\frac{1}{4}$	S 9
S	4				
$\frac{1}{4}$	S 9				
	<p>N. 89° 38' W., beginning new measurement.</p> <p>Descend 74 ft. over SW. slope, through heavy timber and scattering undergrowth.</p>				
4.15	Ravine, drains S. 10° W.; asc. 15 ft. over S. slope.				
6.05	Spur, slopes S.; desc. 87 ft. over broken S. slope.				
10.65	Creek, 2 lks. wide, course S.; desc. 1 ft. over broken S. slope.				
15.30	Ravine, drains S. 20° E.; asce. 436 ft. over SE. slope.				
23.95	Leave timber, enter prairie, edge bears N. and S.				
28.05	Head of ravine, drains S. 30° E.; asc. 137 ft. over SE. face of bluff.				