

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the W. Bdy., T. 27 S., R. 3 W.

CHAINS

from which the 1917 bearing tree:

A fir, 20 ins. diam., bears N. 31° E., 69 lks. dist., with scribe marks $\frac{1}{4}$ visible on opened blaze.

A fir stump, 25 ins. diam., bears S. 37° W., 86 lks. dist., with illegible scribe marks visible on opened blaze. (Record bearing S. 37° E.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

T	27	S
R	4	W
	$\frac{1}{4}$	R
	3	W
S	12	S
	7	
	1958	

*1975
S.L.P. ADDED SURVEY
SEE 672 FILE*

from which

A fir, 9 ins. diam., bears S. $55\frac{1}{4}$ ° E., 14 lks. dist., mkd. $\frac{1}{4}$ S7 BT.

A fir, 11 ins. diam., bears S. $25\frac{1}{2}$ ° W., 77 lks. dist., mkd. $\frac{1}{4}$ S12 BT.

Deposit corner stone alongside iron post.

N. 0° 15' E., beginning new measurement.

Descend 124 ft. over N. slope changing to NW. slope, through scattering timber and dense undergrowth.

10.95 Foot of descent, slopes W.; asc. 166 ft. over broken SW. slope.

24.50 Top of ascent, slopes W.; desc. 182 ft. over NW. slope.

40.25 The corner of secs. 1, 6, 7, and 12, monumented with a sandstone, 16 x 10 x 4 ins., firmly set, 6 ins. above ground, with 5 notches on the S. and 1 notch on the N. edge, from which the remaining 1917 bearing trees:

A fir stump, 32 ins. diam., bears N. 60° E., 94 lks. dist., with scribe marks T 2 visible on a partially opened blaze.

A fir stump, 28 ins. diam., bears N. 19° W., 61 lks. dist., with scribe marks T27S R4W visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

T	27	S
R	4	W
	R	3
	S	1
	S	6
	S	12
	S	7
	1958	

from which

A fir, 13 ins. diam., bears N. $68\frac{1}{2}$ ° E., 128 lks. dist., mkd. T27S R3W S6 BT.

A fir, 11 ins. diam., bears S. 50° E., 142 lks. dist., mkd. T27S R3W S7 BT.