

Dependent Resurvey of a Portion of the W. Bdy., T. 27 S., R. 3 W.

CHAINS

A white oak, 13 ins. diam., bears S. $78\frac{1}{4}^\circ$ W., 295 lks. dist., mkd. T27S R4W S12 BT.

A cedar, 8 ins. diam., bears N. $50\frac{3}{4}^\circ$ W., 214 lks. dist., mkd. T27S R4W S1 BT.

Deposit corner stone alongside iron post.

Land, rolling hills.

Soil, rocky clay.

Timber, fir, cedar, hemlock, maple, madrone, and oak; undergrowth, hazel, madrone, salal, dogwood, vinemaple, poison oak, and chinquapin.

Dependent Resurvey of a Portion of the N. Bdy., T. 27 S., R. 3 W.

(Restoring the 1855 survey by A. R. Flint)

From the corner of secs. 1, 2, 35, and 36, perpetuated by A. Boyer, County Surveyor, in 1936, at record bearing and distance from the original SW. bearing tree, and monumented with a wooden post, 4 x 4 ins. cross section, firmly set, 4 ft. above ground.

from which the original bearing tree:

A down white oak, 18 ins. diam., bears S. 30° W., 202 lks. dist., with an opened blaze, no scribe marks visible.

and county surveyor's bearing trees:

An uprooted fir stump, 16 ins. diam., bears N. 11° E., $2\frac{1}{2}$ lks. dist., with a healed blaze.

A fir stump, 20 ins. diam., bears S. 34° E., 34 lks. dist., with a healed blaze.

A fir snag, 12 ins. diam., bears S. 72° W., 29 lks. dist., with illegible scribe marks visible on opened blaze.

A fir snag, 12 ins. diam., bears N. 36° W., 12 lks. dist., with scribe marks S35 CS BT visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26	S R 3 W
S 35	S 36
S 2	S 1
T 27 S	
1958	

from which

A fir, 20 ins. diam., bears N. $51\frac{1}{2}^\circ$ E., 66 lks. dist., mkd. T26S R3W S36 BT.

A cedar, 12 ins. diam., bears S. $73\frac{1}{4}^\circ$ W., 86 lks. dist., mkd. T27S R3W S1 BT.

A fir, 20 ins. diam., bears S. $30\frac{1}{4}^\circ$ W., 61 lks. dist., mkd. T27S R3W S2 BT.

A fir, 13 ins. diam., bears N. 34° W., 59 lks. dist., mkd. T26S R3W S35 BT.

S. $89^\circ 54'$ W., bet. secs. 2 and 35, marking and blazing true line.