

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the N. Bdy., T. 27 S., R. 3 W.

CHAINS	Descend 242 ft. over SW. slope through heavy timber and dense undergrowth.								
13.15	Graveled and maintained access road, 25 lks. wide, bears NW. curving to N. and SE. curving to S.								
20.425	Point for the E 1/16 sec. cor. of secs. 2 and 35. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table> <tr> <td>E 1/16</td> <td>$\frac{S\ 35}{S\ 2}$</td> </tr> <tr> <td></td> <td>1958</td> </tr> </table> </div> <p>from which</p> <p>A pine, 38 ins. diam., bears N. $0^{\circ} 30'$ E., 140 lks. dist., mkd. E 1/16 S35 BT.</p> <p>A fir, 15 ins. diam., bears S. $47\frac{1}{4}^{\circ}$ W., 41 lks. dist., mkd. E 1/16 S2 BT.</p> <p>Corner falls at foot of descent on S. slope; asc. 33 ft. over SE. slope.</p>	E 1/16	$\frac{S\ 35}{S\ 2}$		1958				
E 1/16	$\frac{S\ 35}{S\ 2}$								
	1958								
26.25	Spur, slopes SW.; desc. 233 ft. over NW. slope,								
40.85	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table> <tr> <td>T 26 S R 3 W</td> <td></td> </tr> <tr> <td>$\frac{1}{4}$</td> <td>$\frac{S\ 35}{S\ 2}$</td> </tr> <tr> <td>T 27 S</td> <td></td> </tr> <tr> <td></td> <td>1958</td> </tr> </table> </div> <p>from which</p> <p>A fir, 50 ins. diam., bears N. $59\frac{1}{2}^{\circ}$ W., 48 lks. dist., mkd. $\frac{1}{4}$ S35 BT.</p> <p>A fir, 30 ins. diam., bears S. $2\frac{1}{2}^{\circ}$ W., 116 lks. dist., mkd. $\frac{1}{4}$ S2 BT.</p> <p>Descend 257 ft. over NW. slope.</p>	T 26 S R 3 W		$\frac{1}{4}$	$\frac{S\ 35}{S\ 2}$	T 27 S			1958
T 26 S R 3 W									
$\frac{1}{4}$	$\frac{S\ 35}{S\ 2}$								
T 27 S									
	1958								
52.50	Creek, 3 lks. wide, course SW.; desc. 18 ft. over SW. slope.								
56.10	Foot of descent, slopes S.; asc. 67 ft. over SE. slope.								
59.90	Leave timber, enter pasture land, edge bears N. and S.								
61.275	Point for the W 1/16 sec. cor. of secs. 2 and 35. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, to bedrock, and in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with brass cap mkd. <div style="text-align: center;"> <table> <tr> <td>W 1/16</td> <td>$\frac{S\ 35}{S\ 2}$</td> </tr> <tr> <td></td> <td>1958</td> </tr> </table> </div> <p>from which</p>	W 1/16	$\frac{S\ 35}{S\ 2}$		1958				
W 1/16	$\frac{S\ 35}{S\ 2}$								
	1958								