

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the N. Bdy., T. 27 S., R. 3 W.

CHAINS	<p>A pine, 17 ins. diam., bears N. 20° E., 183 lks. dist., mkd. W 1/16 S35 BT.</p> <p>A twin oak, 10 ins. diam., bears S. 31$\frac{3}{4}$° E., 119 lks. dist., mkd. W 1/16 S2 BT.</p> <p>The corner falls on a spur, slopes S.; desc. 199 ft. over SW. slope.</p>					
75.75	Graveled and maintained access road, 30 lks. wide, bears NW. and SE.					
81.70	<p>The cor. of secs. 2, 3, 34, and 35, monumented with an iron pipe, 1 in. diam., firmly set, 6 ins. above ground, in a very old mound of stone, 2$\frac{1}{2}$ ft. base, 1 ft. high. Accept this mound of stone as the best available evidence of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground, rebuild the old mound of stone around the iron post, 2$\frac{1}{2}$ ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 26 S R 3 W</td></tr> <tr><td>S 34 S 35</td></tr> <tr><td>S 3 S 2</td></tr> <tr><td>T 27 S</td></tr> <tr><td>1958</td></tr> </table> </div> <p>from which</p> <p>A fir, 26 ins. diam., bears N. 39$\frac{3}{4}$° E., 571 lks. dist., mkd. T26S R3W S35 BT.</p> <p>A twin cedar, 18 ins. diam., bears S. 32$\frac{1}{2}$° E., 425 lks. dist., mkd. T27S R3W S2 BT.</p> <p>A white oak, 14 ins. diam., bears S. 51$\frac{1}{2}$° W., 675 lks. dist., mkd. T27S R3W S3 BT.</p> <p>A white oak, 20 ins. diam., bears N. 66° W., 295 lks. dist., mkd. T26S R3W S34 BT.</p> <p>Deposit iron pipe alongside iron post.</p> <p>Land, rolling hills. Soil, rocky clay. Timber, fir, cedar, hemlock, pine, madrone, maple, alder, and oak; undergrowth, salal, poison oak, madrone, vinemapple, and hazel.</p>	T 26 S R 3 W	S 34 S 35	S 3 S 2	T 27 S	1958
T 26 S R 3 W						
S 34 S 35						
S 3 S 2						
T 27 S						
1958						
	S. 89° 56' W., bet. secs. 3 and 34.					
	Descend 61 ft. over SW. slope, through open pasture land.					
4.50	Asphaltic highway, 35 lks. wide, bears NW. and SE.					
7.95	Oiled access road, 25 lks. wide, bears N. and S.					
9.05	Right bank of Little River, course N.					
10.05	Left bank of Little River; asc. 171 ft. over NE. slope, through scattering timber and dense undergrowth of partially logged area.					
11.25	Graveled access road, 20 lks. wide, bears N. and S.					
19.525	<p>Point for the E 1/16 sec. cor. of secs. 3 and 34.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>					