

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the N. Bdy., T. 27 S., R. 3 W.

CHAINS

A madrone, 35 ins. diam., bears S. 39° E., 79 lks. dist., with an opened blaze, no scribe marks visible.

A white oak, 23 ins. diam., bears S. 27° W., 246 lks. dist., with an opened blaze, no scribe marks visible. (Record distance 237 lks.)

The NW. bearing tree has been dozed out, but found down and out of position and is a black oak, 27 ins. diam., with scribe mark 6 visible on a partially opened blaze.

and locally established bearing trees:

A cedar snag, 20 ins. diam., bears N. 55½° E., 113 lks. dist., with scribe marks T26S R3W S33 CS BT. visible on open blaze.

A cedar, 18 ins. diam., bears S. 55¾° E., 31 lks. dist., with scribe marks T27S R3W S4 CS BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, to bedrock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 26 S R 3 W
S 32 | S 33
S 5 | S 4
T 27 S
1958

from which

A cedar, 6 ins. diam., bears N. 85¼° E., 72 lks. dist., mkd. T26S R3W S33 BT.

A cedar, 16 ins. diam., bears S. 14° E., 94 lks. dist., mkd. T27S R3W S4 BT.

A cedar, 17 ins. diam., bears S. 13½° W., 88 lks. dist., mkd. T27S R3W S5 BT.

A cedar, 22 ins. diam., bears N. 84° W., 334 lks. dist., mkd. T26S R3W S32 BT.

Deposit iron pipe alongside iron post.

Land, rolling hills.

Soil, rocky clay.

Timber, E. ¼ mile, fir, pine, cedar, and scattering madrone, W. ¾ mile, logged and burned; undergrowth, poison oak, vinemaple, blackberry, ocean spray, hazel, salal, and Oregon grape.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 27 S., R. 3 W.

(Restoring the 1855 survey by A. R. Flint
and the 1882 survey by S. C. Flint)

From the corner of secs. 11, 12, 13, and 14, perpetuated and recorded by B. B. Irving, County Surveyor, in 1945, monumented with a stone, 20 x 8 x 8 ins., firmly set, 8 ins. above ground, with 5 grooves on the W. and 2 grooves on the N. face, from which the original bearing trees:

A fir, 45 ins. diam., bears N. 45½° E., 109 lks. dist., bark scribed T27S R3W S12 CS BT. (Record bearing N. 48° E.)