

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 27 S., R. 3 W.

CHAINS

A madrone, 50 ins. diam., bears S.  $10^{\circ}$  W., 32 lks. dist., with a partially opened blaze, no scribe marks visible.

The stump hole and roots of a black oak, bears N.  $5^{\circ}$  W., 54 lks. dist.

and the county surveyor's bearing trees:

A fir, 37 ins. diam., bears S.  $72\frac{1}{2}^{\circ}$  E., 136 lks. dist., bark scribed TS27 R3W S13 CS BT.

A fir, 13 ins. diam., bears S.  $10\frac{1}{2}^{\circ}$  W., 19 lks. dist., with a healed blaze.

A fir, 17 ins. diam., bears N.  $54\frac{3}{4}^{\circ}$  W., 24 lks. dist., with a healed blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap mkd.

T 27 S R 3 W			
S 11	S 12		
S 14	S 13		
1958			

*FD. OK 2/25/86  
R. GEISLER  
C.S. 63/84*

from which

A fir, 7 ins. diam., bears N.  $61\frac{1}{2}^{\circ}$  E., 46 lks. dist., mkd. T27S R3W S12 BT.

A fir, 7 ins. diam., bears S.  $40\frac{1}{4}^{\circ}$  E., 65 lks. dist., mkd. T27S R3W S13 BT.

A fir, 8 ins. diam., bears S.  $64^{\circ}$  W., 6 lks. dist., mkd. T27S R3W S14 BT.

A fir, 13 ins. diam., bears N.  $11\frac{1}{4}^{\circ}$  W., 13 lks. dist., mkd. T27S R3W S11 BT.

Deposit local corner material alongside iron post.

N.  $0^{\circ}$  34' E., bet. secs. 11 and 12, marking and blazing true line.

Ascend 25 ft. over SW. slope, through heavy timber and dense undergrowth.

7.05 Spur ridge, bears NW. and SE.; desc. 348 ft. over NE. slope.

40.16 The  $\frac{1}{4}$  sec. cor. of secs. 11 and 12, perpetuated and recorded by B. B. Irving, County Surveyor, in 1945, monumented with a basalt stone, 14 x 8 x 6 ins., firmly set, 3 ins. above ground at record distance from the two original bearing trees, of which only one remains:

A fir, 20 ins. diam., bears S.  $77^{\circ}$  W., 28 lks. dist., (26 lks. to face), remarked, with a bark scribe by county surveyor,  $\frac{1}{4}$  S11 CS T. (Record bearing S.  $70^{\circ}$  W., 26 lks. dist.)

and county surveyor's bearing tree:

A fir, 42 ins. diam., bears N.  $80\frac{1}{2}^{\circ}$  E., 47 lks. dist., bark scribed  $\frac{1}{4}$  S12 CS BT.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap mkd.