

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 27 S., R. 3 W.

CHAINS

A maple, 13 ins. diam., bears S. 60° E., 160 lks. dist., mkd. T27S R3W S12 BT.

A fir, 6 ins. diam., bears S. 76° W., 132 lks. dist., mkd. T27S R3W S11 BT.

A fir, 7 ins. diam., bears N. 7½° W., 68 lks. dist., mkd. T27S R3W S2 BT.

Deposit local corner material alongside iron post.

Land, rolling hills.

Soil, rocky clay.

Timber, N. portion logged, S. portion fir with scattering cedar, hemlock, oak, pine, maple, and madrone; undergrowth, hazel, vine-maple, poison oak, ocean spray, salal, and Oregon grape.

From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., determined at record bearing and distance from the only remaining original bearing tree, as follows:

A madrone, 20 ins. diam., bears S. 45° W., 175 lks. dist., with scribe marks BT visible on a partially opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

T 27 S	
R 3 W	R 2 W
S 1	S 6
S 12	S 7
1958	

from which

A fir, 12 ins. diam., bears N. 40° E., 155 lks. dist., mkd. T27S R2W S6 BT.

A fir, 12 ins. diam., bears S. 57° E., 87 lks. dist., mkd. T27S R2W S7 BT.

A fir, 15 ins. diam., bears S. 60° W., 36 lks. dist., mkd. T27S R3W S12 BT.

A fir, 10 ins. diam., bears N. 35½° W., 34 lks. dist., mkd. T27S R3W S1 BT.

S. 89° 23' W., bet. secs. 1 and 12.

Ascend 45 ft. over SE. slope through scattering timber and dense undergrowth.

3.25 Spur, slopes S.; desc. 116 ft. over SW. slope changing to W. slope.

10.65 Creek, 3 lks. wide, course SW.; asc. 192 ft. over SE. slope.

19.07 Point for the E 1/16 sec. cor. of secs. 1 and 12.

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

E 1/16	S 1
	S 12
	1958

from which