

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 27 S., R. 3 W.

CHAINS

A fir, 13 ins. diam., bears N. $58\frac{1}{4}^{\circ}$ W., 39 lks. dist.,
mkd. E 1/16 S1 BT.

A fir, 6 ins. diam., bears S. $74\frac{1}{4}^{\circ}$ E., 12 lks. dist.,
mkd. E 1/16 S12 BT.

Ascend 12 ft. over SE. slope.

19.90 Top of ascent slopes S.; desc. 236 ft. over SW. slope.

20.50 Skid road, 15 lks. wide, bears N. and S.

26.80 Skid road, 15 lks. wide, bears NE. and SW.

37.75 Dirt access road, 15 lks. wide, bears N. and S.

38.14 The $\frac{1}{4}$ sec. cor. of secs. 1 and 12, perpetuated with a truck axle,
2 ins. diam., firmly set, 4 ins. above ground, at record bearing
and distance from original bearing trees:

A cedar stump, 36 ins. diam., bears N. 60° W., 64 lks. dist.,
no marks visible.

A cedar stump, 36 ins. diam., bears S. 25° E., 25 lks. dist.,
with old axe marks visible.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the
ground, with brass cap mkd.

T 27 S R 3 W

$\frac{1}{4}$ $\frac{S}{S}$ $\frac{1}{12}$

1958

from which

A fir, 10 ins. diam., bears N. $43\frac{1}{4}^{\circ}$ E., 92 lks. dist.,
mkd. $\frac{1}{4}$ S1 BT.

A fir, 8 ins. diam., bears S. 44° E., 100 lks. dist.,
mkd. $\frac{1}{4}$ S12 BT.

Deposit axle alongside iron post.

N. $89^{\circ} 12'$ W., beginning new measurement.

Descend 28 ft. over SW. slope.

1.80 Creek, 3 lks. wide, course S.; asc. 166 ft. over SE. slope.

11.30 Ridge, bears N. and S.; desc. 180 ft. over NW. slope.

19.365 Point for the W 1/16 sec. cor. of secs. 1 and 12.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the
ground, with brass cap mkd.

W 1/16 $\frac{S}{S}$ $\frac{1}{12}$

1958

from which