

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 27 S., R. 3 W.

CHAINS

A fir, 16 ins. diam., bears N.  $59\frac{1}{2}^{\circ}$  W., 272 lks. dist.,  
mkd. W 1/16 S1 BT.

A fir, 15 ins. diam., bears S.  $23\frac{3}{4}^{\circ}$  E., 103 lks. dist.,  
mkd. W 1/16 S12 BT.

Descend 259 ft. over NW. slope.

27.45 Dirt access road, 20 lks. wide, bears NE. and SW.

37.25 Bond Creek, 5 lks. wide, course SW.; asc. 11 ft. over SE. slope.

38.73 The cor. of secs. 1, 2, 11, and 12.

Land, rolling hills.

Soil, rocky clay.

Timber, fir, cedar, hemlock, madrone, maple, and scattering pine;  
undergrowth, poison oak, hazel, vinemaple, ocean spray, and scat-  
tering manzanita.

N.  $0^{\circ} 18'$  W., bet. secs. 1 and 2.

Ascend 292 ft. over SE. slope, through scattering timber and dense  
undergrowth.

19.94 Point for the S 1/16 sec. cor. of secs. 1 and 2.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the  
ground, with brass cap mkd.

S 1/16  
S 2 | S 1  
1958

from which

A white oak, 14 ins. diam., bears S.  $77\frac{1}{2}^{\circ}$  E., 257 lks.  
dist., mkd. S 1/16 S1 BT.

A pine, 6 ins. diam., bears S.  $41\frac{1}{2}^{\circ}$  W., 177 lks. dist.,  
mkd. S 1/16 S2 BT.

Ascend 233 ft. over SE. slope.

22.10 Abandoned dirt access road, 15 lks. wide, bears E. and W.

25.20 Wire fence, bears E. and W.

32.35 Wire fence, bears E. and W.

39.88 The  $\frac{1}{4}$  sec. cor. of secs. 1 and 2, perpetuated and recorded by  
County Surveyor Boyer at record bearing and distance from the orig-  
inal NE. bearing tree, which is no longer in existence, monumented  
with an iron pipe,  $\frac{3}{4}$  in. diam., firmly set, 12 ins. above ground,  
and in a mound of stone,  $2\frac{1}{2}$  ft. base, to top, from which the county  
surveyor's bearing trees;

A fir stump, 40 ins. diam., bears N.  $51^{\circ}$  E., 121 lks. dist.,  
bark scribed  $\frac{1}{4}$  S1 BT.

A fir snag, 40 ins. diam., bears S.  $63^{\circ}$  W., 70 lks. dist.,  
with scribe marks  $\frac{1}{4}$  S2 CS BT visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the  
ground with brass cap mkd.