


County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 27 S., R. 3 W.

CHAINS

T 27 S R 3 W



Deposit local corner material alongside iron post and raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of corner.

N. $0^{\circ} 50'$ E., beginning new measurement.

Ascend 14 ft. over SW. slope, through dense undergrowth of a logged and burned area.

4.70 Top of ascent, slopes W.; desc. 31 ft. over NW. slope.

10.00 Graveled access road, 20 lks. wide, bears NE. and SW., also foot of descent, slopes W.; asc. 234 ft. over SW. slope.

29.10 Leave logged and burned area, enter timber, edge bears E. and W.

39.01 The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp.


Land, rolling hills.

Soil, rocky clay.

Timber, scattering fir, and hemlock, and logged and burned areas; undergrowth, poison oak, hazel, vinemaple, ocean spray, and manzanita.

From the cor. of secs. 10, 11, 14, and 15, perpetuated and recorded by County Surveyor Byron, in 1957, at record distance from two remaining original bearing trees, monumented with an iron post, 1 in. diam., firmly set, 14 ins. above ground, with brass cap mkd.

County Surveyors



from which the original bearing trees:

A fir, 25 ins. diam., bears S. 68° E., 19 lks. dist., with scribe marks 27S R3W S14 visible on partially opened blaze. (Record bearing S. 55° E.)

A fir, 40 ins. diam., bears N. 38° W., 54 lks. dist., bark scribed T27S R3W S10 BT.

and county surveyor's bearing trees:

A cedar, 12 ins. diam., bears N. 66° E., $43\frac{1}{2}$ lks. dist., with a healed blaze.

A cedar, 12 ins. diam., bears S. 53° W., 29 lks. dist., with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.