

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 27 S., R. 3 W.

CHAINS	<p>A fir, 9 ins. diam., bears N. $14\frac{1}{2}^{\circ}$ E., 67 lks. dist., mkd. N 1/16 S11 BT.</p> <p>A fir, 8 ins. diam., bears S. 69° W., 255 lks. dist., mkd. N 1/16 S10 BT.</p> <p>Descend 108 ft. over NW. slope.</p> <p>62.45 Leave logged area, enter timber, edge bears E. and W.</p> <p>69.85 Jim Creek, 20 lks. wide, course NE. curving to E.; asc. 147 ft. over SE. slope.</p> <p>71.16 From this point the NE. cor. of a wood frame shed, bears S. 77° $12'$ W., $66\frac{1}{2}$ lks. dist., dimensions 81 x 33 ft., long side bears S.</p> <p>From this same point the SW. cor. of a wood frame shed, bears N. 85° E., $45\frac{1}{2}$ lks. dist., dimensions $25\frac{1}{2}$ x 17 ft., long side bears E.</p> <p>73.15 Graveled and maintained access road, 20 lks. wide, bears N. 70° E. and S. 70° W.</p> <p>76.30 Abandoned dirt access road, 20 lks. wide, bears NE. and SW.</p> <p>78.45 Same dirt access road, bears W. and E. curving to SE.</p> <p>80.54 The cor. of secs. 2, 3, 10, and 11, perpetuated and recorded by B. B. Irving, County Surveyor, in 1945, at record bearing and distance from the original bearing trees, monumented with a stone, 24 x 15 x 12 ins., firmly set, with 5 notches on the S., 2 notches on the E., 1 notch on the N., and 4 notches on the W. edge, from which the original bearing trees:</p> <p style="padding-left: 40px;">A rotted fir stump, 12 ins. diam., bears N. 85° E., 19 lks. dist.,</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears S. 65° E., 19 lks. dist., bark scribed T27S R3W S11 CS BT, by the county surveyor.</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears S. 75° W., 17 lks. dist., bark scribed T27S R3W S10 CS BT, by the county surveyor.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 35° W., 17 lks. dist., bark scribed T27S R3W S3 CS BT, by the county surveyor.</p> <p>and county surveyors bearing tree:</p> <p style="padding-left: 40px;">A down fir, 24 ins. diam., bears N. 10° E., 37 lks. dist.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="4">T 27 S R 3 W</td></tr> <tr><td style="border-right: 1px solid black; border-bottom: 1px solid black;">S 3</td><td style="border-bottom: 1px solid black;">S 2</td></tr> <tr><td style="border-right: 1px solid black;">S 10</td><td>S 11</td></tr> </table> <p>1958</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 59° E., 39 lks. dist., mkd. T27S R3W S2 BT.</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. $31\frac{1}{2}^{\circ}$ E., 53 lks. dist., mkd. T27S R3W S11 BT.</p>	T 27 S R 3 W				S 3	S 2	S 10	S 11
T 27 S R 3 W									
S 3	S 2								
S 10	S 11								