

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 27 S., R. 3 W.

CHAINS

A white oak, 7 ins. diam., bears S. 37° W., 125 lks. dist.,
mkd. T27S R3W S10 BT.

A fir, 33 ins. diam., bears N. $12\frac{1}{2}^{\circ}$ W., 55 lks. dist.,
mkd. T27S R3W S3 BT.

Deposit county surveyor's corner stone alongside iron post.

Land, rolling hills.

Soil, rocky clay.

Timber, fir, and scattering cedar, hemlock, oak, maple, madrone,
and alder; undergrowth, hazel, vinemaple, dogwood, ocean spray,
poison oak, rhododendron, Oregon grape, and salal.

From the cor. of secs. 1, 2, 11, and 12.

S. $89^{\circ} 44'$ W., bet. secs. 2 and 11.

Ascend 57 ft. over SE. slope, through logged area and dense under-
growth.

12.65 Ravine, drains SE.; asc. 3 ft. over SE. slope.

14.15 Spur, slopes S.; desc. 121 ft. over SW. slope.

31.80 Foot of descent, slopes S.; asc. 33 ft. over SE. slope.

36.80 Spur, slopes S.; desc. 62 ft. over SW. slope.

40.28 The $\frac{1}{4}$ sec. cor. of secs. 2 and 11, perpetuated and recorded by
F. C. Frear, County Surveyor, in 1943 and 1955, at record bearing
and distance from the original SW. bearing tree, which is no longer
in existence, monumented with an iron pipe, $\frac{3}{4}$ in. diam., firmly
set, 8 ins. above ground, from which the locally established bearing
trees, as follows:

A cedar, 14 ins. diam., bears S. 86° E., 98 lks. dist.,
with scribe marks $\frac{1}{4}$ cor sec 2 BT visible on opened blaze.

A white oak, 10 ins. diam., bears S. $8\frac{1}{4}^{\circ}$ W., 180 lks. dist.,
with scribe marks S11 BT visible on a partially opened blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground,
with brass cap mkd.

T 27 S R 3 W

$\frac{1}{4}$ $\frac{S}{S}$ $\frac{2}{11}$

1958

*FD OK 4/28/76 Co. SURVEYOR
C.S. 59/B*

from which

A fir, 15 ins. diam., bears N. 19° E., 247 lks. dist.,
mkd. $\frac{1}{4}$ S2 BT.

A cedar, 18 ins. diam., bears S. $44\frac{1}{2}^{\circ}$ E., 201 lks. dist.,
mkd. $\frac{1}{4}$ S11 BT.

Deposit local corner material alongside iron post.

S. $89^{\circ} 08'$ W., beginning new measurement.

Descend 20 ft. over SW. slope, through open pasture land.