

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 27 S., R. 3 W.

CHAINS

County Surveyors

 $\frac{1}{4}$ S

3 | 2

T 27 S R 3 W

1954

Office

from which the original bearing tree:

A fir, 17 ins. diam., bears N. 80° E., 71 lks. dist.,
with axe marks visible on an opened blaze.

and county surveyor's bearing trees:

A yew, 6 ins. diam., bears S. 49° E., 46 lks. dist.,
with scribe marks $\frac{1}{4}$ S2 CS BT visible on open blaze.

A fir, 10 ins. diam., bears S. 76 $\frac{1}{2}$ ° W., 163 $\frac{1}{2}$ lks. dist.,
with scribe marks $\frac{1}{4}$ S3 CS BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 25 ins. in the ground,
with brass cap mkd.

T 27 S R 3 W

 $\frac{1}{4}$

S 3 | S 2

1958

from which

A cedar, 6 ins. diam., bears N. 74 $\frac{1}{2}$ ° E., 94 lks. dist.,
mkd. $\frac{1}{4}$ S2 BT.

A fir, 37 ins. diam., bears S. 39° W., 99 lks. dist.,
mkd. $\frac{1}{4}$ S3 BT.

Deposit county surveyor's iron pipe alongside iron post.

North, beginning new measurement.

Ascend 124 ft. over SE. slope.

- 4.45 Spur, slopes E.; desc. 356 ft. over NE. slope.
- 13.60 Dirt access road, 20 lks. wide, bears NW. and SE., also leave timber and enter pasture land, edge bears NW. and SE.
- 21.20 Dirt access road, 25 lks. wide, bears E. and W. curving to NW.
- 25.50 Left bank of Little River, course W. curving to NW.
- 26.50 Right bank of Little River, 48 ft. over SW. slope.
- 28.60 Paved access road, 30 lks. wide, bears NW. and SE.
- 35.35 Asphaltic highway, 35 lks. wide, bears NW. and SE.
- 40.24 The cor. of secs. 2, 3, 34, and 35, on N. bdy. of the Tp.

Land, rolling hills.

Soil, rocky clay.

Timber, scattering fir, cedar, hemlock, madrone, oak, alder, and maple; undergrowth, poison oak, hazel, salal, madrone, and Oregon grape.